

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **G024**
 Product name: **Ceramic grease 400 ml**
 Chemical name and synonym: **Lubricant**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Ceramic spray grease for parts that are exposed to high pressures or at very high temperatures.**

| Identified Uses | Industrial | Professional | Consumer |
|------------------|------------|--------------|----------|
| Industrial Use | ✓ | - | - |
| Professional Use | - | ✓ | - |

1.3. Details of the supplier of the safety data sheet

Name: **AMBRO-SOL S.R.L.**
 Full address: **Via per Pavone del Mella n.21**
 District and Country: **25020 Cigole (BS)**
Italia

Tel. +39 030 9959674

Fax +39 030 959265

e-mail address of the competent person
 responsible for the Safety Data Sheet

quality@ambro-sol.com

1.4. Emergency telephone number

For urgent inquiries refer to

Centro Antiveleni di Pavia: 0382 24444 (IRCCS Fondazione Maugeri - Pavia)
Centro Antiveleni di Bergamo: 800 883300 (Ospedali Riuniti - Bergamo)
Centro Antiveleni di Firenze: 055 7947819 (Ospedale Careggi - Firenze)
Centro Antiveleni di Roma: 06 3054343 (Policlinico Gemelli - Roma)
Centro Antiveleni di Napoli: 081 7472870 (Ospedale Cardarelli - Napoli)
Centro de Información Toxicológica en España: 91 5620420 (Inst. Nacional de Toxicología y Ciencias Forenses)
Centre Antipoison en France: 01 40054848 (Centre Antipoison et de Toxicovigilance de Paris)
Pomorskie Centrum Toksykologii ul. Kartuska 4/6, 80-104 Gdańsk tel./fax: (58) 682 04 04
American Association of Poison Control Centers: +1 (800) 222-1222
Giftkontrollzentrum Berlin, Brandenburg 030 – 19 240

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

G024 - Ceramic grease 400 ml

| | | |
|--|--------------|---|
| Aerosol, category 1 | H222 H229 | Extremely flammable aerosol. Pressurised container: may burst if heated. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H336 | May cause drowsiness or dizziness. |
| Hazardous to the aquatic environment, chronic toxicity, category 2 | H411 | Toxic to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

| | |
|-------------|--|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: may burst if heated. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements:

| | |
|------------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P251 | Do not pierce or burn, even after use. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. |
| P211 | Do not spray on an open flame or other ignition source. |
| P273 | Avoid release to the environment. |
| P391 | Collect spillage. |
| P102 | Keep out of reach of children. |

Contains: Hydrocarbons, C6, isoalkanes

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CLP.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification 1272/2008 (CLP) |
|-------------------------------------|------------------|---|
| Hydrocarbons, C6, isoalkanes | | |
| CAS 64742-49-0 | $27 \leq x < 31$ | Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P |
| EC 265-151-9 | | |
| INDEX 649-328-00-1 | | |
| Reg. no. 012119484651-34-XXXX | | |
| PROPANE | | |
| CAS 74-98-6 | $23 \leq x < 27$ | Flam. Gas 1 H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U |
| EC 200-827-9 | | |
| INDEX 601-003-00-5 | | |
| Reg. no. 01-2119486944-21-0046 | | |
| BUTANE | | |
| CAS 106-97-8 | $11 \leq x < 15$ | Flam. Gas 1 H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U |
| EC 203-448-7 | | |
| INDEX 601-004-00-0 | | |
| Reg. no. 01-2119474691-32-XXXX | | |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 37,70 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use.

Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

| | | |
|-----|----------------|--|
| DEU | Deutschland | TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte |
| ESP | España | INSHT - Límites de exposición profesional para agentes químicos en España 2017 |
| FRA | France | JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits |
| POL | Polska | ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r |
| EU | TLV-ACGIH | ACGIH 2018 |
| | RCP TLV | ACGIH TLVs and BEIs – Appendix H |

Hydrocarbons, C6, isoalkanes

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | |
|---------|---------|--------|-----|------------|-----|
| | | mg/m3 | ppm | mg/m3 | ppm |
| OEL | EU | | | 72 | |
| RCP TLV | | 1200 | | | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | | 1301 mg/kg bw/d | | | | |
| Inhalation | | | | 1137 mg/m3 | | | | 5306 mg/m3 |
| Skin | | | | 1377 mg/kg bw/d | | | | 13964 mg/kg bw/d |

PROPANE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | |
|-----------|---------|--------|------|------------|------|
| | | mg/m3 | ppm | mg/m3 | ppm |
| AGW | DEU | 1800 | 1000 | 7200 | 4000 |
| MAK | DEU | 1800 | 1000 | 7200 | 4000 |
| NDS | POL | 1800 | | | |
| TLV-ACGIH | | | 1000 | | |

BUTANE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | |
|------|---------|--------|-----|------------|-----|
| | | mg/m3 | ppm | mg/m3 | ppm |

| | | | | | |
|-----------|-----|------|------|------|------|
| AGW | DEU | 2400 | 1000 | 9600 | 4000 |
| MAK | DEU | 2400 | 1000 | 9600 | 4000 |
| VLA | ESP | | 1000 | | |
| VLEP | FRA | 1900 | 800 | | |
| WEL | GBR | 1450 | 600 | 1810 | 750 |
| NDS | POL | 1900 | | 3000 | |
| TLV-ACGIH | | | 1000 | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|---------------------------|
| Appearance | aerosol |
| Colour | white/ivory |
| Odour | characteristic of solvent |
| Odour threshold | Not available |

G024 - Ceramic grease 400 ml

| | |
|--|------------------------------|
| pH | Not available |
| Melting point / freezing point | Not available |
| Initial boiling point | Not available |
| Boiling range | Not available |
| Flash point | < 0 °C |
| Evaporation Rate | Not available |
| Flammability of solids and gases | flammable gas |
| Lower inflammability limit | Not available |
| Upper inflammability limit | Not available |
| Lower explosive limit | Not available |
| Upper explosive limit | Not available |
| Vapour pressure | Not available |
| Vapour density | Not available |
| Relative density | a 20°C 0,64 ÷ 0,68 g/ml g/ml |
| Solubility | insoluble in water |
| Partition coefficient: n-octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | Not available |
| Explosive properties | not applicable |
| Oxidising properties | not applicable |

9.2. Other information

| | |
|------------------------------|--------------------------|
| Total solids (250°C / 482°F) | 32,60 % |
| VOC (Directive 2010/75/EC) : | 67,40 % - 444,84 g/litre |
| VOC (volatile carbon) : | 49,98 % - 329,84 g/litre |

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

BUTANE

LC50 (Inhalation) > 1442,738 mg/l/15min rat

PROPANE

LC50 (Inhalation) 800000 ppm 15 min

Hydrocarbons, C6, isoalkanes

LD50 (Oral) > 2000 mg/kg bw rat

LD50 (Dermal) > 2000 mg/kg bw rabbit

LC50 (Inhalation) > 25 mg/l/4h air (rat)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

BUTANE

LC50 - for Fish > 24,11 mg/l/96h

PROPANE

LC50 - for Fish 85,82 mg/l/96h

EC50 - for Crustacea 41,82 mg/l/48h

Hydrocarbons, C6, isoalkanes

LC50 - for Fish 8,41 mg/l/96h

EC50 - for Crustacea 4,7 mg/l/48h

EC50 - for Algae / Aquatic Plants > 12 mg/l/72h

Chronic NOEC for Algae / Aquatic Plants 6,47 mg/l

12.2. Persistence and degradability

PROPANE

Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

BUTANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

PROPANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

Hydrocarbons, C6, isoalkanes

Rapidly degradable

12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water 1,09

PROPANE

Partition coefficient: n-octanol/water 1,09

12.4. Mobility in soil

Hydrocarbons, C6, isoalkanes

Partition coefficient: soil/water 1,78

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are considered hazardous special waste. Do not dispose of in wastewater.

Empty cylinders, although completely emptied, should not be dispersed in the environment.

The overheated aerosol container at a temperature above 50 °C may burst even if it contains a small gas residue.

Waste transport may be subject to ADR.

Refer to applicable regulations.

European Waste Catalog (contaminated containers):

Aerosol as a household waste is excluded from the application of the above standard.

The exhausted commercial / industrial aerosol can be classified as: 15.01.10 *: packaging containing residues of dangerous or contaminated substances.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS (Hydrocarbons, C6, isoalkanes)
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous
IMDG: Marine Pollutant
IATA: NO



For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID: HIN - Kemler: --

Limited Quantities: 1 L

Tunnel restriction code: (D)

IMDG: Special Provision: -

EMMS: F-D, S-U

Limited Quantities: 1 L

| | | | |
|-------|-----------------------|--------------------------|-----------------------------|
| IATA: | Cargo: | Maximum quantity: 150 Kg | Packaging instructions: 203 |
| | Pass.: | Maximum quantity: 75 Kg | Packaging instructions: 203 |
| | Special Instructions: | A145, A167, A802 | |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Gas 1 | Flammable gas, category 1 |
| Aerosol 1 | Aerosol, category 1 |
| Aerosol 3 | Aerosol, category 3 |
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Press. Gas (Liq.) | Liquefied gas |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic toxicity, category 2 |
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: may burst if heated. |
| H225 | Highly flammable liquid and vapour. |
| H280 | Contains gas under pressure; may burst if heated. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 03 / 08 / 09 / 11 / 12 / 14 / 15.