



XT-10 (S161) 10 functions in 1 5 LT



UNLOCKING: One of the best Ambro-Sol products, the XT-10 is a multipurpose lubricant with a strong unlocking power: mechanism and hitch won't be a problem! Never without XT-10, at home and in the office.

PROTECTIVE: This product protects surfaces and materials from atmospheric agents, bad weather, dust and use: thanks so the XT-10 all that won't be a problem. This Ambro-Sol product has a strong protective power, and it's ideal for all surfaces and situations..

LUBRICANT: This Ambro-Sol product has a strong lubricant power, and it's ideal for maintenance and lubrication of all surfaces and for all types of uses, at home and at work. It can't miss in your garages!

PENETRATE: It's not enough to act: it's indispensable that the product operates! With Ambro-Sol XT-10 you have the guarantee of a strong penetrating product. XT-10 product acts on all types of surfaces, and it resolves the problem at the origin..

DEGREASE: Are you cyclers or motorcycles? Or, simply, do you need a functional product with a strong degrease power? Then the Ambro-Sol XT-10, multipurpose product, is for you!

HIGH TEMPERATURE RESISTANT: XT-10 doesn't fear rivals, in particular with high temperature: this amazing multipurpose product has a great advantage, it resists with very hot temperature, and for that it's perfect to be used in welding sector, and in mechanical and electric sectors.

ANTI CORROSIVE: Are your materials under consumption and corrosion process? Ambro-Sol has the solution for you! The XT-10 product has a strong anti-corrosive power. Try it!!

HYDRO-REPELLENT: This product acts with water! The Ambro-Sol XT-10 makes surfaces, applications and materials protect from water and from atmospheric agents.

ANTI-SEIZE: XT-10 has a strong anti-seize power, and it's ideal for all type of materials: it unblock immediately every application. The Ambro-Sol XT-10 is ideal for professional uses and also for domestic uses.

SOLVENT POWER: Rust is the enemy of everyone. But with the XT-10 fight it is very simple: this amazing multipurpose product has a strong solvent power, and it permits to dissolve dust but also other materials as silicone, glue, adhesives, paints...





XT-10 (S161) 10 functions in 1 5 LT

XT10 – 10 functions: unlocking, protective, lubricating, penetrating, degreasing, high temperature resistant, anti-corrosion, waterproof, anti-scuff, great solvent power (it dissolves rust). With the active ingredients of the highest quality, it has an ultra lubricant power, ultra penetrating degreaser and it is perfectly suited to the workshop, at home, in the garage, in the garden, in the nautical industry, heavy industry wherever there is a mechanism that requires maintenance.

CERTIFIED:

Test N° 14LA05748

E.P. Properties and anti-seize with “four ball tester”



INNOVHUB
STAZIONI SPERIMENTALI
PER L'INDUSTRIA



STAZIONE SPERIMENTALE
PER LE INDUSTRIE DEGLI OLI E DEI GRASSI

Innovazione e ricerca

Technical Specifications:

| | |
|----------------------|-------------------------------|
| Quantity | 5 LT |
| Barcode | EAN 13: 8034108892566 |
| Confection | 1 pz |
| Aspect | Metal Tank |
| Color | Straw yellow |
| Odour | Characteristic of solvent |
| Relative Density | at 20°C 0,79 ÷ 0,83 g/ml |
| Flash Point | > 61° C |
| Vapor tension | 0,5 hPa a 20°C |
| Ignition temperature | > 200 °C |
| Viscosity | < 8 mm ² /s a 40°C |

ASTM D 2783-03

| Test / Method | Un.measure | Result |
|------------------|------------|-------------|
| Speed | laps/min | 1760 |
| Time of test | s | 10 |
| Engage load | kgf | 50 |
| Weld load | kgf | 160 |
| Load load / wear | kgf | 30 |

ASTM D 4172-94

| Test / Method | Un.measure | Result |
|-------------------------|------------|-------------|
| Speed | laps/min | 1200 |
| Time of test | min | 60 |
| Load / Charge | kgf | 40 |
| Temperature room | / | / |
| Diam. Medium Wear track | mm | 0,86 |

XT10[®]
10 FUNZIONI IN 1

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

- H226** Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.

This information, even if reliable, must be considered only approximate. The usage does not imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.