

Lithium multipurpose grease (G013)

Do you need a grease for many different uses? This Ambro-Sol product is for you: it's ideal for lubricate parts of car, industrial machines and farming machines. It's waterproof and it protects from dust and bad weather.



HOW TO USE: shake and spray directly on the surface from a distance of 15 - 25 cm. The product could be sprayed also whit straw (posted in a multi straw cap).

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under zero degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.	
H229	Pressurized container: may burst if heated.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H412	Harmful to aquatic life with long lasting effects.	

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.



Ambro-Sol - 25020 Cigole (BS) Italy - <u>www.gnocchiecospray.com</u> - <u>www.ambro-sol.com</u> - <u>info@ambro-sol.com</u>

Quantity	400 ml
Barcode	EAN 13: 8034108892290
Confection	12 pz

LITHIUM MULTIPURPOSE GREASE - A compound of high quality saponified greases. Grease with a wide spectrum of uses, good chemical stability, water-repellent and adhesive. It protects against water and it is perfectly stable and resistant in brine and dirty atmospheres. It resist against acid and basic solution and atmospheric corrosion. Ideal for lubricating, bearing, bushes, hubs, kingpins, guides and general use on motor vehicles, farming and industrial machinery.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	a 20°C 0,71 ÷ 0,75 g/ml
Flash point	Low.0° C
Pressure at 20°C	4/6 bar
Consistency	NLGI EP2 (base synthetic lithium soap)
Penetration at 25°C 0.1 mm	265-295
Drip point	+ 190°C
Application temperature	-40°C - +180°C