Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 1/12

S157 – Lubricant unblocking 7 functions 500 ml HQ

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: \$15

Product name Sbloccante Lubrificante 7 funzioni

Chemical name and synonym penetrating unlocking

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use lubricant

1.3. Details of the supplier of the safety data sheet

Name GNOCCHI ECO- SPRAY S.R.L. Full address Via per Pavone del Mella sn

District and Country 25020 Cigole (BS)

Italia

Tel. +39 030 9959674 Fax +39 030 959265

e-mail address of the competent person

responsible for the Safety Data Sheet info@gnocchiecospray.com

1.4. Emergency telephone number

For urgent inquiries refer to CENTRO ANTIVELENI Ospedale Niguarda tel: +39 02 66101029

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.

Aspiration hazard, category 1 H304 May be fatal if swallowed and enters airways.

Specific target organ toxicity - single exposure, category 3 H336 May cause drowsiness or dizziness.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.





Signal words:

Danger

Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 2/12

S157 – Lubricant unblocking 7 functions 500 ml HQ

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P301+P310 IF SWALLOWED: immediately call a POISON CENTER / doctor / . . .

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

Contains: NAPHTHA (PETROL.) HYDROTREATED HEAVY

MINERAL OIL NAPHTENIC

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CI P

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification. Conc. %. Classification 1272/2008

(CLP).

NAPHTHA (PETROL.) HYDROTREATED HEAVY

CAS. 64742-48-9 40 - 42,5 Flam. Liq. 3 H226, Asp. Tox.

1 H304, STOT SE 3 H336,

Note P

EC. 919-857-5

INDEX. 649-327-00-6

Reg. no. 01-2119463258-33-XXXX

BUTANE

CAS. 106-97-8 22,5 - 24 Flam. Gas 1 H220, Note C U

EC. 203-448-7

INDEX. 601-004-00-0

S157 - Lubricant unblocking 7 functions 500 ml HQ

Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 3/12

PROPANE

CAS. 74-98-6 22,5 - 24 Flam. Gas 1 H220, Note U

EC. 200-827-9

INDEX. 601-003-00-5

MINERAL OIL NAPHTNENIC

CAS. 64742-53-6 15 - 16,5 Asp. Tox. 1 H304

EC. 265-156-6 INDEX. -

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

${\bf 5.2. \ Special \ hazards \ arising \ from \ the \ substance \ or \ mixture.}$

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

S157 - Lubricant unblocking 7 functions 500 ml HQ

Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 4/12

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

7.3. Specific end use(s).

Revision nr. 10 Dated 01/02/2016

Printed on 23/02/2016 Page n. 5/12

S157 - Lubricant unblocking 7 functions 500 ml HQ

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU Deutschland MAK-und BAT-Werte-Liste 2012

ESP España INSHT - Límites de exposición profesional para agentes químicos en

España 2015

FRA JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 France

United Kingdom EH40/2005 Workplace exposure limits GRB

ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia POL Polska

16 grudnia 2011r

TLV-ACGIH **ACGIH 2014**

NAPHTHA (PETROL) HYDROTREATED HEAVY

Threshold Limit Value.	JKO IKLAILD	IIEAV I			
Туре	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	DEU	300	50	600	100
NDS	POL	300		900	

PROPANE

Threshold Limit Value. Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
NDS	POL	1800				
TLV-ACGIH			1000			

BUTANE

20171112					
Threshold Limit Value.					
Туре	Country	TWA/8h		STEL/15min	l
		mg/m3	ppm	mg/m3	ppm
		mg/mo	ppiii	1119/1110	ppiii
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
		= . 30			
VLA	ESP		800		
VLEP	FRA	1900	800		
WEL	GRB	1450	600	1810	750
NDS	POL	1900		3000	
TLV-ACGIH				2377	1000

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 6/12

S157 - Lubricant unblocking 7 functions 500 ml HQ

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

$\bf 9.1.$ Information on basic physical and chemical properties.

Appearance aerosol Colour grey

Odour characteristic of solvent Odour threshold. Not available.

Not available. Melting point / freezing point. Not available. Initial boiling point. Not applicable. Boiling range. Not available Flash point. Not applicable. Evaporation Rate Not available. Flammability of solids and gases Not available. Lower inflammability limit. Not available Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Not available. Relative density. Solubility Not available Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Not available. Decomposition temperature. Not available. Viscosity Explosive properties Not available. Oxidising properties Not available.

9.2. Other information.

VOC (Directive 2010/75/EC) : 85,00 % VOC (volatile carbon) : 70,83 %

Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 7/12

S157 – Lubricant unblocking 7 functions 500 ml HQ

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

Avoid overheating.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

NAPHTHA (PETROL.) HYDROTREATED HEAVY LD50 (Oral).> 5000 mg/kg Rat LD50 (Dermal).> 2000 mg/kg Rabbit

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or

Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 8/12

S157 - Lubricant unblocking 7 functions 500 ml HQ

contaminate soil or vegetation.

12.1. Toxicity.

NAPHTHA (PETROL.) HYDROTREATED HEAVY

8,2 mg/l/96h Pimephales promelas LC50 - for Fish. 4,5 mg/l/48h Daphnia magna EC50 - for Crustacea.

EC50 - for Algae / Aquatic 3,1 mg/l/72h Pseudokirchnerella subcapitata

12.2. Persistence and degradability.

BUTANE

Solubility in water. mg/I 0,1 - 100

Rapidly biodegradable.

PROPANE

Solubility in water. mg/I 0,1 - 100

Rapidly biodegradable.

NAPHTHA (PETROL.) HYDROTREATED HEAVY Rapidly biodegradable.

12.3. Bioaccumulative potential.

BUTANE

Partition coefficient: n-1,09

octanol/water.

PROPANE

Partition coefficient: n-1,09

octanol/water.

12.4. Mobility in soil.

NAPHTHA (PETROL.) HYDROTREATED HEAVY

Partition coefficient:

soil/water.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

1,78

12.6. Other adverse effects.

Revision nr. 10 Dated 01/02/2016

Printed on 23/02/2016

Page n. 9/12

S157 - Lubricant unblocking 7 functions 500 ml HQ

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA:

1950

14.2. UN proper shipping name.

ADR / RID:

AEROSOLS.

FLAMMABLE **AEROSOLS**

IMDG: IATA:

AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es).

ADR / RID:

Class: 2

Label: 2.1

IMDG:

Class: 2

Label: 2.1

IATA:

Class: 2

Label: 2.1



14.4. Packing group.

ADR / RID, IMDG,

IATA:

14.5. Environmental hazards.

ADR / RID:

NO

IMDG: IATA:

NO

14.6. Special precautions for user.

ADR / RID:

HIN - Kemler: --

Limited

Tunnel

Revision nr. 10 Dated 01/02/2016

Printed on 23/02/2016

Page n. 10/12

S157 - Lubricant unblocking 7 functions 500 ml HQ

Quantities: 1

restriction code: (D)

Special Provision: -

IMDG: EMS: F-D, S-U Limited Quantities: 1

Cargo:

Maximum quantity: 150 Packaging instructions: 203

Pass.:

Kg Maximum quantity: 75

Packaging instructions:

203

Kg

A145, A167,

A802

Special Instructions:

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

IATA:

Point.

40

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Revision nr. 10 Dated 01/02/2016

Printed on 23/02/2016

Page n. 11/12

S157 - Lubricant unblocking 7 functions 500 ml HQ

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1 Flammable gas, category 1 Aerosol 1 Aerosol, category 1 Aerosol 3 Aerosol, category 3

Flam. Lig. 3 Flammable liquid, category 3 Asp. Tox. 1 Aspiration hazard, category 1

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament

Revision nr. 10

Dated 01/02/2016

Printed on 23/02/2016

Page n. 12/12

S157 - Lubricant unblocking 7 functions 500 ml HQ

- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.