



7 functions lubricant unlocking HQ 500 ml(S157)

Seven functions in only one spray included in the Ambro-Sol High quality line; this product is ideal for professional uses and for domestic uses, in particular for the cure of your garden. It lubricates, degreases, unblocks, and much more, to answer to every eventuality.



Quantity	500 ml
Barcode	EAN 13: 8034108891712
Confection	12 pz

7 FUNCTIONS LUBRICANT UNLOCKING HQ – Unlocking / lubricant spray with 7 functions with 360° dispensing valve: unblocking, protective, lubricating, penetrating, degreasing, high temperature resistant, non-corrosive. Thanks to MOS2 and graphite, it has an ultra power, ultra lubricant, ultra penetrating and unlocking capacity; it is perfectly suited for workshop, home, garage, garden, in the marine, heavy industry or wherever there is a mechanism that requires maintenance.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Dark grey
Odour	Characteristic of solvent
Relative density	at 20°C 0,68 ÷ 0,71 g/ml
Flash point	Low.0° C
Pressure at 20°C	3/5 bar
Viscosity	< 8 mm ² /s a 40°C
Vapor tension	0,5 hPa a 20°C
Solubility	Insoluble in water
Operating temperature	- 60°C / + 220°C

Test ASTM D 2783-03	Un.misura	Results
Speed	giri/min	1760
Test duration	s	10
Meshing load	kgf	50
Welding load	kgf	160
Load-Wear Index	kgf	23

HOW TO USE: Shake well before use. Sprinkle the product on the part to treat, leave act for some minutes, therefore in the case of rusted pieces proceed to the unlocking, eventually in presence of more resistant scaling, repeat the operation. The product can also be disbursed with sectional straw (inserted in the cork fine-straw). **PRECAUTIONS:** Don't apply on instruments in tension. Don't apply on material overheated.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H336	May cause drowsiness or dizziness.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.