



PTFE grease 1kg (G018)

This is the 1 L version of this Ambro-Sol grease: low friction coefficient, high chemical inertia, excellent resistance to high loads. Used on bearings, bushes, conveyor rollers in the steel, glass, ceramic and brick industries.

Quantity	900 g
Barcode	EAN 13: 8034108892641
Confection	8 pz



PTFE GREASE – Composed of special high-boiling temperature fluids. It doesn't leaves residues and acts perfectly even at temperatures higher than +250°C. It gives a low friction coefficient, high chemical inertia and excellent resistance to high loads. Used on bearings, bushes, conveyor rollers in the steel, glass, ceramic and brick industries.

Technical Specifications:

Aspect	Metal jar
Color	Light brown/Orange
Odour	Odourless
Relative density	at 20°C 0,88 ÷ 0,92 g/ml
Flash point	>200° C
Solubility	Insoluble in water
Consistence	NLGI EP2
Penetration at 25°C 0.1 mm	265 - 295 mm/10
Drip point	> 270°C
Application temperature	-40°C - + 250°C

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under zero degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.