



## PTFE lubricant (L050)

Do you need a spray to lubricate parts under strong pressure? Then this Ambro-Sol product is for you! It prevents freezing and corrosion, it removes creaks and it prevents short circuit and malfunctioning.



Quantity	400 ml
Barcode	EAN 13: 8034108890081
Confection	12 pz

**PTFE LUBRICANT** – It creates a lubricating, transparent film that prevents dirt from depositing. Particularly suited for the lubrication of parts subjected to high pressure. It prevents rubber parts from freezing and corrosion by salt water. It prevents short-circuits and malfunctions caused by humidity in electrical conductors. It eliminates squeaking, and it's water repellent and silicone-free. Also it facilitates the insertion of cables and cords inside sheathes. Particularly indicated for the maintenance of tools, gaskets and seals in general, door hinges and locks.

### Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Light white
Odour	Characteristic of solvent
Relative density	a 20°C 0,62 ÷ 0,66 g/ml
Flash point	Low. 0° C
Pressure at 20°C	4/6 bar
Melting point	ASTM D4591 deg C 334,70
PTFE Average particle size	INTERN micron 3,0 +/- 2
Specific gravity	ASTM D4894 g/cm <sup>3</sup> 2,18 +/- 0,05
Melting point PTFE	327°C GD 340 °C
Maximum temperature	400°C(peaks)

**HOW TO USE:** Shake the cylinder at least one minute. Dispense the product from a distance of about 20 cm. Wait the distension of the product on the surface. If necessary, repeat the operation.

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

### Hazards identification:

H222	<b>Extremely flammable aerosol.</b>
H229	<b>Pressurized container: it may burst if heated.</b>
H315	<b>Causes skin irritation.</b>
H336	<b>May cause drowsiness or dizziness.</b>
H411	<b>Toxic to aquatic life with long lasting effects.</b>

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.