

This spray has an high lubricant and protective power, and it's ideal for all main materials. This product is hydro repellent and it prevents accumulation of electrostatic charge.



HOW TO USE: shake well the can. Spray directly on the surface to be treated from a distance of 15 - 25 cm. The product can be dispensed also with a straw (straw inserted in the multi-cap).

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children. Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.



Ambro-Sol - 25020 Cigole (BS) Italy - www.gnocchiecospray.com - www.ambro-sol.com - info@ambro-sol.com

Quantity

Barcode

Confection

SPRAY SILICON - Pure silicone-based oil solution with anti-

adhesive qualities, separating and lubricating properties, that can be used on a variety of materials. It acts as an excellent water repellent and prevents the accumulation of electrostatic charges. It is also effective when used as polish and protector of plastic components. It protects gaskets from cracking and at the same time increases their sealing gualities and life.

200 ml

12 pz

EAN 13: 8034108890135

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Colorless
Odour	Characteristic of solvent
Relative density	a 20°C 0,62 ÷ 0,66 g/ml
Flash point	Low.0° C
Pressure at 20°C	4/6 bar
Viscosity silicone	350 - 400 mm2/s a 25°C
Auto-ingnition temperature	> 400 ° C (for the dry residue)
Steam pressure	<0.01 kPa a 20°C
Freezing point	ca -50°C
Water solubility	Insoluble