



Cutting oil 400 ml (OL104)

This Ambro-Sol spray is ideal for hard metal cutting and operations. It's perfect for hydraulic sector and for steel sector.



Quantity	400 ml
Barcode	EAN 13: 8034108890159
Confection	12 pz

CUTTING OIL – HEAVY-DUTY PROTECTIVE TOOL LUBRICANT-

New product developed for specific professional applications in hard metal cutting and operations. Oil with a paraffin mineral base enriched with special EP anti-weld additives. Ideal for use in difficult threading operations with particularly hard, alloy steel. Suited for the use in the hydraulic sector.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	a 20°C 0,64 ÷ 0,68 g/ml
Flash point	Low. 0° C
Pressure at 20°C	4/6 bar
Pour point	< - 10°C
Viscosity Oil at 40°C	288 - 352 cst
Max temperature	>300°C(Oil Content)
Initial boiling point	>250°C(at atmosferic pressure)

HOW TO USE: shake the can well. Spray directly on the surface to be treated from a distance of 15 - 25 cm. The product can be dispensed also with a straw (straw inserted in the multi-cap).

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: it may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use