



Washable cutting oil (OL112)

Easily washable product, specifically designed to be used in processes such as drilling, threading, milling, cutting of hard metals and stainless steel. Another product of the home Ambro-Sol from lubricity.



| | |
|------------|-----------------------|
| Quantity | 400 ml |
| Barcode | EAN 13: 8034108892542 |
| Confection | 12 pz |

WASHABLE CUTTING OIL – Specific product for processing like drilling, threading, milling and cutting ferrous materials. Composed of mineral oils with high lubricity it is used effectively even in manual and semi-automatic jobs. It is specifically used in the plumbing industry for threaded pipes. It lubricates the materials by lowering the temperature and eliminating vibration. Delete any corrosive effect exerting a good protective action on the workpiece. The solution is emulsified. The product is fully washable and removable with water.

Technical Specifications:

| | |
|--------------------------|--|
| Aspect | Cylinder containing under pressure fluid |
| Color | straw yellow |
| Odour | Characteristic of solvent |
| Relative density | a 20°C 0,68 ÷ 0,72 g/ml |
| Flash point | Low.0° C |
| Pressure at 20°C | 4/6 bar |
| Flash point | >150°C(content oil) |
| Relative density at 25°C | 0,900 ÷ 0,050 (Content oil) |
| Water solubility | Emulsione parziale oleosa (content il) |
| Self-ignition | 360° c.a. |

HOW TO USE: Shake the cylinder. Spray directly on surface to be treated from a distance of 15 - 25 cm. The product can also it is provided with drinking straw (Inserted in the multi-straw cap). Completely removable with water after use.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children

Hazards identification:

| | |
|------|--|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurized container: may burst if heated. |
| H336 | May cause drowsiness or dizziness. |

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use