



Unlocking 400 ml (S152)

400 ml spray with a big unlocking and protective power for mechanicals parts. It removes rust and oxidations.



Quantity	400 ml
Barcode	EAN 13: 8034108890203
Confection	12 pz

UNLOCKING – Penetrating synthetic fluid with a high solvent and releasing power, it facilitates the releasing process of nuts, bolts, joints, threads, hinges and all other mechanical parts affected by rust and oxidation. It also leaves a lasting water-proof and water repellent protective film.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	a 20°C 0,68 ÷ 0,72 g/ml
Flash point	Low.0° C
Pressure at 20°C	4/6 bar
Melting/freezing point	< -66°C (liquid base)
Boiling point	176°C circa (liquid base)
Vapor tension	> 5 bar (20°C)
Viscosity	< 1 cSt - 9 cSt 40°C (liquid base)
Solubility	Insoluble in water
Operating temperature	-50°C / +130 °C c.a.
Flash point	40 °C (liquid base)

HOW TO USE Shake well before use. Spray the product on the part to treat, leave for a few minutes, then in the case of rusted parts proceed with the unlocking, in presence of more resistant deposits repeat the operation. The product can be also be sprayed with sectional straw (Inserted in the multi-straw cap). **PRECAUTIONS:** Do not apply to equipment in tension. Do not apply to materials overheated.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H336 May cause drowsiness or dizziness.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.