



Unlocking 5 lt (S155)

This unlocking and protective fluid is contained in the provision format. It can be used on mechanical parts, it protects from humidity and fire and also removes rust and oxidations.



Quantity	5 Lt
Barcode	EAN 13: 8034108891644
Confection	11 pz

UNLOCKING – Penetrating synthetic fluid with a high solvent and releasing power, it facilitates the releasing process of nuts, bolts, joints, threads, hinges and all other mechanical parts affected by rust and oxidation. It also leaves a lasting water-proof and water repellent protective

Technical Specifications:

Aspect	Tin-plate tank
Color	Straw yellow
Odour	Characteristic of solvent
Relative density	a 20°C 0,80 ÷ 0,84 g/ml
Flash point	>60 °C
Melting/freezing point	-52°C ~
Vapor tension	0,5 hPa (20°C)
Viscosity	> 9 cSt 40°C
Solubility	Insoluble in water
Operating temperature	-50°C / +130 °C c.a.
Ignition temperature	>200 °C
Boiling temperature	+160 / +245 °C
Boiling point	>170 °C

HOW TO USE: application with brush or spray. Apply the product on the part to be treated, leave for a few minutes, then in the case of rusted parts proceed to unlock, with resistant rust repeat the operation. The product is ready to use. To further dilute the product use mineral turpentine.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.