



Thermal shock unlocking (S154)

Do you need a product to remove deep rust? Don't worry: this Ambro-Sol spray helps you for this problem, and at the same time it lubricates the surface.



Quantity	400 ml
Barcode	EAN 13: 8034108890227
Confection	12 pz

THERMAL SHOCK UNLOCKING – A new product for the removal of persistent and stratified rust; high penetrating and lubricating power; the product, sprayed at a temperature of about -40°C , freezes and helps the removal of the rust.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	a 20°C $0,60 \pm 0,64$ g/ml
Flash point	Low. 0°C
Pressure at 20°C	5,5 bar
Melting/freezing point	From -187°C to -138°C
Boiling point	Around 176°C (liquid base)
Vapor tension	> 5 bar (20°C)
Viscosity	< 1 cSt - 9 cSt 40°C (liquid base)
Solubility	Insoluble in water
Operating temperature	-60°C / $+130^{\circ}\text{C}$ c.a.
Flash point	32°C (liquid base)

HOW TO USE Shake well before use. Spray the product on the part to treat, leave for a few minutes, then in the case of rusted parts proceed with the unlocking, in presence of more resistant deposits repeat the operation. The product can be also be sprayed with sectional straw (Inserted in the multi-straw cap). **PRECAUTIONS:** Do not apply to equipment in tension. Do not apply to materials overheated.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C , after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H336	May cause drowsiness or dizziness.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.