



Foamy cable sliding lubricant (S156)

This spray is ideal for electric contacts: it removes friction and at the same time it doesn't ruin materials, protects and lubricates. This product is ideal in particular for electricians.



HOW TO USE Shake proper mind-the can before use. Spray the foam directly on the cables or in the tunnels concerned and start with the operations entering or slip-off. The product can be supplied fitted with an-that straw (straw inserted in the multi-cap).

Quantity	400 ml
Barcode	EAN 13: 8034108891477
Confection	12 pz

CABLE SLIDING LUBRICANT – It eliminates friction and makes rubber and plastic electric cables easy to slide. It does not damage synthetic cable insulation. Excellent protection that slows down natural ageing processes.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	White
Odour	Oudouless
Relative density	a 20°C 0,87 ÷ 0,91 g/ml
Flash point	Low.0° C
Pressure at 20°C	4/6 bar
viscosity	1-100 cps (25°C) (liquid base)
Density active base	Ca. 1,0 g/cm3
Water solubility	Miscibile
Boiling point	Ca. 100 °C (liquid base)
PH	7 - 8,5 (liquid base)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222 **Extremely flammable aerosol.**
H229 **Pressurized container: may burst if heated.**

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before usina. the users have to verivy the suitability of the product for the specific use.