



Plastic coating transparent (I270)

Spray paint plasticizer, which protects against oxidation and corrosion due to weather conditions. It forms an invisible and flexible film ideal for protecting metals such as copper, silver, aluminum and bronze. It also protects other materials such as paper, stone, wood and plastic. It does not become yellow.



HOW TO USE: Clean the surface to be treated with synthetic thinner. Turn the bottle and shake it well until the marbles move freely inside the cylinder then spray a few times and proceed with the delivery. To prevent dripping, apply two thin coats from a distance of 20-30 cm.

PLASTIC COATING TRANSPARENT – It is the protective and invisible film-paint, that protects against rusting and the corrosive effects of atmospheric agents. It does not become yellow. It forms a flexible film used for metals such as silver, copper, bronze and aluminum. It protects wood, plastic, stone, paper.

Technical Specifications:

Quantity	400 ml
Barcode	EAN 13: 8034108893655
Confection	12 PZ
Aspect	Cylinder containing under pressure fluid
Color	Transparent
Odour	Typical of solvent
Relative density	a 20°C 0,72 ÷ 0,76 g/ml
Flash point	Less than 0° C
Pressure at 20°C	4/6 bar/4/6 bar
Dry residue in the bottle	About 6%
Brilliance	About 90 gloss
Thickness	About 9 micron
Suitable materials	wood, metal, iron, aluminum, steel, glass, plastics, paper materials.
Operating temperature	-10°C / +100°C (Picchi 120° C)
Drying times	Out of dust 10 minutes
	Dry on touch 15 minutes
	Dry on depth 22 hours

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.