GNOCCHI EC	O- SPRAY S.R.L.	Revision nr. 5 Dated 22/02/2016
	400 1	Printed on 25/02/2016
1256 – Paint	remover 400 ml	Page n. 1/12
	Safety data sheet	
SECTION 1. Identification of the subs	stance/mixture and of the compa	any/undertaking
1.1. Product identifier		
Code:	1256	
Product name Chemical name and synonym	Sverniciatore 400 ml	
	decapante	
1.2. Relevant identified uses of the substance or m Intended use maintenance	-	
1.3. Details of the supplier of the safety data sheet Name	GNOCCHI ECO- SPRAY S.R.L.	
Full address	Via per Pavone del Mella sn	
District and Country	25020 Cigole (BS) Italia	
	Tel. +39 030 9959674	
	Fax +39 030 959265	
e-mail address of the competent person		
responsible for the Safety Data Sheet	info@gnocchiecospray.com	
1.4. Emergency telephone number For urgent inquiries refer to	CENTRO ANTIVELENI Ospedale Niguarda	tel: +39 02 66101029
SECTION 2. Hazards identification.		
2.1. Classification of the substance or mixture.		

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words:

Danger

I256 – Paint remover 400 ml

Revision nr. 5

Dated 22/02/2016

Printed on 25/02/2016 Page n. 2/12

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H319	Causes serious eye irritation.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P264	Wash thoroughly after handling.
P280	Wear eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.
P337+P313	If eye irritation persists: Get medical advice / attention.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
1 410 1 412	

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
DME		
CAS. 115-10-6	45 - 47,5	Flam. Gas 1 H220, Press. Gas H280
EC. 204-065-8		
INDEX. 603-019-00-8		
1,3 DIOXALANE		
CAS. 646-06-0	40 - 42,5	Flam. Liq. 2 H225, Eye Irrit. 2 H319
EC. 211-463-5		
INDEX. 605-017-00-2		
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT		
CAS. 64742-49-0	1 - 1,5	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Note P
EC. 265-151-9		
INDEX. 649-328-00-1		

Reg. no. 012119484561-34-xxxx

Revision nr. 5 Dated 22/02/2016

1256 - Paint remover 400 ml

Printed on 25/02/2016

Page n. 3/12

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

1256 – Paint remover 400 ml

Revision nr. 5

Dated 22/02/2016

Printed on 25/02/2016 Page n. 4/12

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en

		GNOCC	HI ECO- S	PRAY S.F	R.L.			rision nr. 5 ed 22/02/2016	
1256 – Paint remover 400 mi							Printed on 25/02/2016 Page n. 5/12		
POL EU	Polska OEL EU TLV-ACGIł	1	16 grudnia	ĄDZENIE M 2011r)09/161/EU;)00/39/EC.	INISTRA PR Directive 20			DŁECZNEJ z 004/37/EC;	dnia
1,3 DIOXAL									
Threshold I Type	limit value.	Country	TWA/8h		STEL/15min				
			mg/m3	ppm	mg/m3	ppm			
AGW		DEU	310	100	620	200			
MAK		DEU	310	100	620	200			
VLA		ESP	61	20					
NDS		POL	10		50				
TLV-ACGIH			61		20				
NAPHTHA	PETROLEUM),	HYDROTREATE	D LIGHT						
Threshold I					OTEL /1Emin				
Туре		Country	TWA/8h		STEL/15min				
~ =-			mg/m3	ppm	mg/m3	ppm			
OEL		EU			72				
Health - De	rived no-effect l	evel - DNEL / DI Effects on consumers.	MEL			Effects on workers			
Route of expo	sure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.		1301 mg/kg/d	1301 mg/kg/d		Systemic		Systemic		Systemic
Inhalation.				1137 mg/m3	1137 mg/m3			5306 mg/m3	5306 mg/m3
Skin.		1377 mg/kg/d	1377 mg/kg/d					13964 mg/kg/d	13964 mg/kg/d
egend:									
C) = CEILINC	G ; INHAL = Inf	nalable Fraction	; RESP = Res	pirable Fraction	າ ; THORA =	Thoracic Frac	tion.		
ND = hazard	identified but no	DNEL/PNEC av	ailable ; NEA	= no exposure	expected ; N	PI = no hazaro	d identified.		

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

Revision nr. 5

1256 – Paint remover 400 ml

Dated 22/02/2016

Printed on 25/02/2016

Page n. 6/12

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance Colour Odour threshold. pH. Melting point / freezing point. Initial boiling point. Boiling range. Flash point. Evaporation Rate Flammability of solids and gases Lower inflammability limit. Upper inflammability limit. Upper explosive limit. Upper explosive limit. Upper explosive limit. Vapour pressure. Vapour density Relative density. Solubility Partition coefficient: n-octanol/water Auto-ignition temperature. Decomposition temperature. Viscosity Explosive properties Oxidising properties 9.2. Other information.	aerosol white characteristic of solvent Not available. Not available. Not available. Not applicable. Not applicable. Not available. Not available.
VOC (Directive 2010/75/EC) :	86,00 %
VOC (volatile carbon) :	43,53 %

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

1256 – Paint remover 400 ml

Revision nr. 5

Dated 22/02/2016

Printed on 25/02/2016

Page n. 7/12

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

Avoid overheating.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product. Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

1,3 DIOXALANE LD50 (Oral).> 2000 mg/kg Rat LC50 (Inhalation).68,4 mg/l Rat - Sprague-Dawley

SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

1,3 DIOXALANE

LC50 - for Fish.

EC50 - for Crustacea.

12.2. Persistence and degradability.

- > 95,4 mg/l/96h Lepomis macrochirus
- > 772 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants.

> 877 mg/l/72h Pseudokirchnerella subcapitata

GNOCCHI ECO- SPRAY S.R.L.	Revision nr. 5
	Dated 22/02/2016
l256 – Paint remover 400 ml	Printed on 25/02/2016
	Page n. 8/12

1,3 DIOXALANE

NOT rapidly biodegradable.

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT Rapidly biodegradable.

12.3. Bioaccumulative potential.

1,3 DIOXALANE

Partition coefficient: n- -0,31 octanol/water.

12.4. Mobility in soil.

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT Partition coefficient: soil/water.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

1,78

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, 1950 IATA:

14.2. UN proper shipping name.

ADR / RID:

AEROSOLS,

I256 – Paint remover IMDG: FLAMMABLE IATA: AEROSOLS, FLAMMABLE FLAMMABLE 14.3. Transport hazard class(es). ADR / RID: Class: 2 Label: 2.1		Printed on 25/02/2016 Page n. 9/12
FLAMMABLE IMDG: AEROSOLS IATA: AEROSOLS, FLAMMABLE		Page n. 9/12
IMDG: AEROSOLS IATA: AEROSOLS, FLAMMABLE AEROSOLS, 4.3. Transport hazard class(es).	•	
FLAMMABLE	*	
	*	
ADR / RID: Class: 2 Label: 2.1	٠	
	1	
IMDG: Class: 2 Label: 2.1		
IATA: Class: 2 Label: 2.1	*	
4.4. Packing group.	•	
ADR / RID, IMDG, - IATA:		
4.5. Environmental hazards.		
ADR / RID: NO		
IMDG: NO		
IATA: NO		
14.6. Special precautions for user.		
ADR / RID: HIN - Kemler:	Limited Quantities: 1	Tunnel restriction code: (D)
Special Provision: -	L	
IMDG: EMS: F-D, S-U	Limited Quantities: 1 L	
IATA: Cargo:	L Maximum quantity: 150 Кg	Packaging instructions: 203
Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
Special Instructions:	A145, A167,	200

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

8

I256 – Paint remover 400 ml

Revision nr. 5

Dated 22/02/2016

Printed on 25/02/2016 Page n. 10/12

Restrictions relating to the product	or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.	
Product. Point.	40	
Substances in Candidate List (Art. s	<u>59 REACH).</u>	
None.		
Substances subject to authorisarior	n (Annex XIV REACH).	
None.		
Substances subject to exportation r	reporting pursuant to (EC) Reg. 649/2012:	
None.		

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas	Pressurised gas
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

1256 – Paint remover 400 ml

Revision nr. 5

Dated 22/02/2016

Printed on 25/02/2016

Page n.	11/12
---------	-------

H229	Pressurised container: may burst if heated.	
H225	Highly flammable liquid and vapour.	
H280	Contains gas under pressure; may burst if heated.	
H304	May be fatal if swallowed and enters airways.	
H319	Causes serious eye irritation.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
 ADR: European Agreement concerning the carriage of Dangerous goods by Road CAS NUMBER: Chemical Abstract Service Number CE50: Effective concentration (required to induce a 50% effect) CE NUMBER: Identifier in ESIS (European archive of existing substances) CLP: EC Regulation 1272/2008 DNEL: Derived No Effect Level EmS: Emergency Schedule GHS: Globally Harmonized System of classification and labeling of chemicals IATA DGR: International Air Transport Association Dangerous Goods Regulation IC50: Immobilization Concentration 50% IMDG: International Maritime Code for dangerous goods IMO: International Maritime Organization INDEX NUMBER: Identifier in Annex VI of CLP 		
- LC50: Lethal Concentration 50%		
	H225 H280 H304 H319 H315 H336 H411 LEGEND: - ADR: European Agreemen - CAS NUMBER: Chemical J - CE50: Effective concentrat - CE NUMBER: Identifier in - CLP: EC Regulation 1272/ - DNEL: Derived No Effect L - EmS: Emergency Schedul - GHS: Globally Harmonized - IATA DGR: International A IC50: Immobilization Conc - IMDG: International Maritime - INDEX NUMBER: Identifie	

- LD50: Lethal dose 50%

- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament

- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

GNOCCHI ECO- SPRAY S.R.L.	Revision nr. 5
	Dated 22/02/2016
I256 – Paint remover 400 ml	Printed on 25/02/2016
	Page n. 12/12

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 01 / 03 / 08 / 12 / 16.