

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: I254
 Product name: Multipurpose permanent glue
 Chemical name and synonym: Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Permanent multipurpose adhesive (thermoplastic rubber in solvent)

Identified Uses	Industrial	Professional	Consumer
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name: Ambro-Sol s.r.l.
 Full address: Via per Pavone del Mella n.21
 District and Country: 25020 Cigole (BS)
 Italia
 Tel. +39 030 9959674
 Fax +39 030 959265

e-mail address of the competent person

responsible for the Safety Data Sheet

quality@ambro-sol.com

1.4. Emergency telephone number

For urgent inquiries refer to

Centro Antiveleni di Pavia: 0382 24444 (IRCCS Fondazione Maugeri - Pavia)
 Centro Antiveleni di Bergamo: 800 883300 (Ospedali Riuniti - Bergamo)
 Centro Antiveleni di Firenze: 055 7947819 (Ospedale Careggi - Firenze)
 Centro Antiveleni di Roma: 06 3054343 (Policlinico Gemelli - Roma)
 Centro Antiveleni di Napoli: 081 7472870 (Ospedale Cardarelli - Napoli)
 Centro Antiveleni in Spagna: 91 5620420 (Inst. Nacional de Toxicología y Ciencias Forenses)
 Centro Antiveleni in Francia: 01 40054848 (Centre Antipoison et de Toxicovigilance de Paris)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

I254 – Multipurpose permanent glue**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER / doctor / . . .
P331	Do NOT induce vomiting.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

Contains: NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ACETONE

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CLP.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.1. Substances**

Information not relevant

3.2. Mixtures

I254 – Multipurpose permanent glue

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification**Classification 1272/2008 (CLP)****PROPANE**

CAS 74-98-6

23 ≤ x < 27

Flam. Gas 1 H220, Press.
Gas (Liq.) H280, Note U

EC 200-827-9

INDEX 601-003-00-5

Reg. no. 01-2119486944-21-XXXX

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

CAS 64742-49-0

20 ≤ x < 23

Flam. Liq. 2 H225, Asp. Tox.
1 H304, Skin Irrit. 2 H315,
STOT SE 3 H336, Aquatic
Chronic 2 H411, Note P

EC 265-151-9

INDEX 649-328-00-1

Reg. no. 012119484561-34-XXXX

ACETONE

CAS 67-64-1

15 ≤ x < 19

Flam. Liq. 2 H225, Eye Irrit. 2
H319, STOT SE 3 H336,
EUH066

EC 200-662-2

INDEX 606-001-00-8

Reg. no. 01-2119471330-49-XXXX

BUTANE

CAS 106-97-8

9 ≤ x < 11

Flam. Gas 1 H220, Press.
Gas (Liq.) H280, Note C U

EC 203-448-7

INDEX 601-004-00-0

Reg. no. 01-2119474691-32-XXXX

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 33,29 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

I254 – Multipurpose permanent glue

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits

I254 – Multipurpose permanent glue

Oral	VND	62 mg/kg				
Inhalation	VND	200 mg/m ³	VND	2,420 mg/m ³	VND	1,210 mg/m ³
Skin	VND	62 mg/kg			VND	186 mg/kg

BUTANE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
VLA	ESP		800		
VLEP	FRA	1900	800		
WEL	GBR	1450	600	1810	750
NDS	POL	1900		3000	
TLV-ACGIH				2377	1000

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

I254 – Multipurpose permanent glue**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Colour	colourless
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	flammable gas
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	a 20°C 0,66 ÷ 0,70 g/ml
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	240 - 300 mPa·s. (Brookfield RVT)
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information

VOC (Directive 2010/75/EC) :	73,31 % - 491,18 g/litre
VOC (volatile carbon) :	56,96 % - 381,64 g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

10.4. Conditions to avoid

Avoid overheating.

ACETONE

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE

Incompatible with: acids, oxidising substances.

10.6. Hazardous decomposition products

ACETONE

May develop: ketenes, irritant substances.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component)

LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component)

LD50 (Oral) of the mixture: Not classified (no significant component)

LD50 (Dermal) of the mixture: Not classified (no significant component)

PROPANE

I254 – Multipurpose permanent glue

800000 ppm 15 min
LC50 (Inhalation)

ACETONE
5800 mg/kg bw
LD50 (Oral)
7426 mg/kg bw guinea pig
LD50 (Dermal)
50,1 mg/l/4h air
LC50 (Inhalation)

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
3790 mg/kg bw rat
LD50 (Oral)
3500 mg/kg bw rabbit
LD50 (Dermal)
34,73 mg/l/4h air (rat)
LC50 (Inhalation)

SKIN CORROSION / IRRITATION

Causes skin irritation
SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation
RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class
GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class
CARCINOGENICITY

Does not meet the classification criteria for this hazard class
REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class
STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness
STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class
ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

BUTANE
LC50 - for Fish 85,82 mg/l/96h
EC50 - for Crustacea 41,82 mg/l/48h

PROPANE
LC50 - for Fish 85,82 mg/l/96h

I254 – Multipurpose permanent glue

EC50 - for Crustacea 41,82 mg/l/48h

ACETONE

LC50 - for Fish 6,83 g/l
 EC50 - for Crustacea 8,8 g/l/48h
 Chronic NOEC for Crustacea 1,659 g/l 28 days

**NAPHTHA (PETROLEUM),
HYDROTREATED LIGHT**

LC50 - for Fish 8,41 mg/l/96h
 EC50 - for Crustacea 4,7 mg/l/48h
 EC50 - for Algae / Aquatic
 Plants 15,65 mg/l/72h
 Chronic NOEC for Algae /
 Aquatic Plants 6,47 mg/l

12.2. Persistence and degradability**BUTANE**

Solubility in water 0,1 - 100 mg/l
 Rapidly biodegradable

PROPANE

Solubility in water 0,1 - 100 mg/l
 Rapidly biodegradable

ACETONE

Rapidly biodegradable

**NAPHTHA (PETROLEUM),
HYDROTREATED LIGHT**

Rapidly biodegradable

12.3. Bioaccumulative potential**BUTANE**

Partition coefficient: n-
 octanol/water 1,09

PROPANE

Partition coefficient: n-
 octanol/water 1,09

ACETONE

Partition coefficient: n-
 octanol/water -0,23

I254 – Multipurpose permanent glue

BCF 3

12.4. Mobility in soilNAPHTHA (PETROLEUM),
HYDROTREATED LIGHTPartition coefficient:
soil/water 1,78**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**ADR / RID, IMDG, 1950
IATA:**14.2. UN proper shipping name**ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS,
FLAMMABLE**14.3. Transport hazard class(es)**

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1



I254 – Multipurpose permanent glue

IATA: Class: 2 Label: 2.1

**14.4. Packing group**ADR / RID, IMDG, -
IATA:**14.5. Environmental hazards**ADR / RID: NO
IMDG: NO
IATA: NO**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 100 Kg	Packaging instructions: 130
	Pass.:	Maximum quantity: 25 Kg	Packaging instructions: 130
	Special Instructions:	A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product
Point 40Substances in Candidate List (Art. 59 REACH)Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

I254 – Multipurpose permanent glue

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas (Liq.)	Liquefied gas
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

I254 – Multipurpose permanent glue**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.