



Multipurpose permanent glue (I254)

This spray is amazing! It dries immediately. It can be used on different materials and it resists to high temperature. These are its secrets, you just have to try it!



HOW TO USE: Shake well before use. Clean the part to glue. Sprinkle the product on one of the surfaces to glue. Overlap the other one sticking on the glued part practicing a strong pressure. The initial taking is rapid but the complete adhesion happens within 24 hours.

Quantity	400 ml
Barcode	EAN 13: 8034108890296
Confection	12 pz

MULTIPURPOSE PERMANENT GLUE – Particularly indicated for bonding of rubber, metal, vinyl, fabric, wood, and plastic materials. Elevated heat resistance even with prolonged exposure. Also highly resistant to plasticizers in general. Complete with adjustable button.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Colorless
Odour	Characteristic of solvent
Relative density	a 20°C 0,66 ± 0,70 g/ml
Flash point	Low.0° C
Pressure at 20°C	4/6 bar
Dry residue	38 - 40 %
Viscosity at 20°C	240 - 300 mPa.s. (Viscometer Brookfield RVT).
Tack (ropiness)	Very strong
Taking	rapid
Drying times	Min. 3' – Max 6'
Adhesive type	Rubber thermoplastic adhesive in solvent
Range temperature	÷ 80°C (peak)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 35°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	It may cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.