

## Anti-slip compound for belts (I255)

Do you have some problems on belts of various materials? Don't worry: Ambro-Sol will help you! With this spray you'll have a perfect adherence on belts, and also a long-term protective action.



**HOW TO USE** shake well the product before use, clean the strap before the use, apply the product along the inside surface of the strap

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under zero degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

### Hazards identification:

<b>H222</b>	<b>Extremely flammable aerosol.</b>
<b>H229</b>	<b>Pressurized container: may burst if heated.</b>
<b>H319</b>	<b>Causes serious eye irritation.</b>
<b>H336</b>	<b>May cause drowsiness or dizziness.</b>
<b>H412</b>	<b>Harmful to aquatic life with long lasting effects.</b>
<b>EUH066</b>	<b>Repeated exposure may cause skin dryness or cracking.</b>

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.

Quantity	400 ml
Barcode	EAN 13: 8034108891460
Confection	12 pz

**ANTI-SLIP COMPOUND FOR BELTS** – It guarantees a perfect adhesion of leather, rubber, fabric and nylon belts keeping constant the synchronism between the moving parts. Suitable for trapezoid and flat belts, it lengthens both belt life and effectiveness as it enters the pores thus preventing cuts and crackings.

### Technical Specifications:

Aspect	Cylinder can containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	a 20°C 0,68 ÷ 0,72 g/ml
Flash point	Low. 0° C
Pressure at 20°C	4/6 bar
Viscosity at 23°C	5,000 – 20,000 cps (dry residue)
Application temperature	-30 °C ÷ +110 °C (dry residue)
Shear rate D	25 s-1
Solubility	Insoluble in water