



Cyanoacrylate activator (I269)

How can you accelerate the glue action of cyanoacrylic adhesives? It is so simple, thanks to this product included in the Ambro-Sol "Adhesive" line. You can apply it before and after the glue action, and it guarantees a long term fixing.



Quantity	200 ml
Barcode	EAN 13: 8034108892702
Confection	12 pz

CYANOACRYLATE ACTIVATOR – Cyanoacrylate adhesives activator is a product designed to promote the speed of action of cyanoacrylate adhesives. It can be applied before or after gluing. Product free of amines, especially suitable when high speed adhesiveness is required. It is often used, before or after gluing, to ensure a rapid process of chemical cross-linking and fixing. This product is not suitable for adhesives that are chlorine-based or highly oxidizing product.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Transparent
Odour	Characteristic of solvent
Relative density	a 20°C 0,68 ± 0,72 g/ml
Flash point	0° C
Pressure at 20°C	4/6 bar
Vapor pressure	250 hPa (20°C)
Stringiness at 25°C	0,700 mm2/s SIO D445 (ASTM D445)
Active ingredient <1%	CH ₃ C ₆ H ₄ N(CH ₃) ₂ (pure at 99%)
Refractive index	n ₂₀ /D 1.525 lt. (dry residue)

HOW TO USE: Shake well before use. The surfaces must be dry cleaned. Avoid contact of the adhesive with the activator. Do one or two coats of activator on both the surfaces to be glued. Be sure to treat with the activator throughout the area to be glued. Leave for 1-2 minutes the surface treated. So now apply adhesive cyanoacrylate following the profile of our Codes I264, I265, I266. The activator may attack some surfaces, first test on a hidden part of the object.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under zero degrees, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.