



## Inox-stainless steel spray (Z352)

Ambro-Sol spray are created to answer to every requirement of use: in particular, this product protects surfaces from corrosion and atmospheric agents, and it dries rapidly.

**INOX-STAINLESS STEEL SPRAY** – This zinc coating is silicone resin based and it forms a protective layer. Formulated to remain unchanged over time with exceptional resistance to chemical corrosion and weathering and good mechanical strength. Quick drying coating.



### Technical specifications:

Quantity	400ml
Confection	12 pz
Barcode	EAN 13 8034108890364
Aspect	Cylinder containing under pressure fluid
Physical state	Pigmented liquid in aerosol
Flash point	Low. 0° C
Pressure	at 20°C 5,5 bar
Relative density	at 20°C 0,73 ÷ 0,77 g/ml
Propellant	GPL
Chemical nature	Synthetic resin with inhibiting pigment of corrosion based of zinc dust
Colour	steel
Powder purity Zn	> 98%
Odour	Characteristic of solvent
Zinc percentage	Dry residue 18%
Resistance temperature	300 °C (peak 400° C)
Resa per bombola	2 / 3 mq2
Drying times = 20°	Out dust: 10' Dry to touch: 20' Dry in depth: 6 hour

#### APPLICATION FIELDS:

Surfaces in metal as iron, aluminum, steel.  
Protection of ferrous metallic structures, pipelines, eaves, enclosures, job utensils etc.

**HOW TO USE:** Clean carefully the support to treat for eliminating encrusting and traces of rust through synthetic thinner. If it's necessary sanding it with abrasive's paper. To turn upside-down the cylinder and to shake it well until the marbles can move freely inside the cylinder, spray a couple of times and progress with the painting. To avoid dropping spray twice from a distance from the support of about 20-30cm. After the use spray for 2/3 seconds with the cylinder turned upside-down to prevent the dispenser to block.

#### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

#### Hazards identification:

H222	<b>Extremely flammable aerosol.</b>
H229	<b>Pressurized container: may burst if heated.</b>
H319	<b>Causes serious eye irritation.</b>
H336	<b>May cause drowsiness or dizziness.</b>
EUH066	<b>Repeated exposure may cause skin dryness or cracking.</b>

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.