



Mirror leafing effect enamel (V400MET)

Do you want to donate brilliance to surfaces and various objects? Decoupage? Are you the artists of the Christmas holidays? This is the spray for you! Ideal for materials that are inside of buildings and dwellings, dries quickly and acts deeply. Many effects in gold and silver base, which will amaze you!

MIRROR LEAFING EFFECT ENAMEL - It is a metallic enamel characterized by a particular brightness that made the enamel similar to a mirror. Good adhesion, it is used on all materials except for the non-stick material (Poletilene, etc..). AMBRO-SOL LEAFING is the bright enamel for indoor and outdoor that beautify and brightens the most different surfaces and objects: frame, furniture, iron, vases, mask, cups, medals, Christmas ornaments and other. It dries to the touch in roughly 15 minutes and it dries fully in roughly 45 minutes. N.B.: the particular ness of this enamel doesn't provide any kind of protection from abrasions. Once applied, it should not be exposed outside, hadled or over painted.



Directive 2004/42/CE: C.O.V.
 Under category: Special finishing
 Limit value COV: 840 g/Liter
 Max effective contents: 640 g/Liter

FIELDS OF APPLICATION:

Wood surfaces, metal surfaces as iron, aluminum, steel, glass and plastics.

Technical specifications:

Quantity	400 ml
Packing	6 Pz.
Aspect	Cylinder containing under pressure fluid
Chemical nature	Very fast drying acrylic paints
Colour	Various
Odour	Characteristic of solvent
Relative density	At 20°C 0,72 ÷ 0,76 g/ml
Flash point	Low. 0° C
Writing on spray bottom	Barcode, production date, product name
Pressure	at 20°C 5,5 ± 0,5 bar
Pressure	at 50°C 8,0 ± 0,5 bar
Viscosity Ford cup	From 10" to 13"
Dry residual in spray	From 20% to 28%
Granulometry grindometer	Bottom Scale 0 a 2 Micron
Gloss	From 20 to 100 Gloss (Glossmeter angle 60°)
Thickness 1 hand	13 Micron
Thickness 3 hands	36 Micron
Resistance temperature	-10°C / +200°C (Peak 250° C)
Drying times:	Out dust 15 minutes
	Dry to touch 18 minutes
	Dry in depth 22 hours
Security cap child-proof patented	
Token dye reference	
Is possible have different type of actuators for various effects and employ	

Advice for use: clean accuracy the surface to be treated, the surface must be completely dry. If you want to apply the product on plastic surface it advisable to use an anchor primer for plastics (V400PRIMER.2).

For mirror/chrome products (V400MET.3 e V400MET.5) if you apply more than once on the same surface, the final mirror effect is more evident.

ISTRUCTIONS FOR USE:

1. Open the cap:
break 3 safety seals-clips to open the cap.

2. Shake well before use the spray at least 1 minute,
until the internal balls can move freely.
It's recommended to shake the product even during
use.



Break three safety seals clips to open the cap.



3. Spray the product:

4. Pratical advices for use:



Dispensing: linear
Quantity product dispensed: medium
Dispensing type: medium cone
Spray type: nebulized

-Apply a first hand/coat light to improve coverage and adherence, to reduce the possibility of dropping. Apply from a distance of 20 cm.

-after a few moment apply a second horizontal hand/coat immediately followed by a third vertical hand-coat.

-Let dry a few minutes.



Dispensing: linear
Quantity product dispensed: low
Dispensing type: medium cone
Spray type: nebulized

- After use, it's advisable to spray for 2/3 seconds with the spray upside down, to avoid the block of the actuator.

-After 24h, proceed with the normal use of painted piece.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under zero degrees and over 45°, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.