



Paint refill (V402)

Ambro-Sol paints don't finish! This Ambro-Sol spray pre-refilled with components and solvents compatibles with every types of paints (added by the seller). You won't have excuse for your domestic works and for professional works.

REFILL PAINT - Prefilled bottle with 300 ml mix of solvents, propellants and additives, compatible with most of paints: acrylic, nitro-acrylic, nitro-synthetic, nitrocellulose. The reseller adds the paint according to the required color. In case of special filling the color can slightly change. After the paint filling we recommend to use the product in the short period.



Technical specifications:

Quantity	300 ml in origin, 400 ml after the fill
Confection	12 Pz.
Aspect	Cylinder containing under pressure fluid
Propellant	DME(dimethyl ether)
Color	Colorless
Odour	Characteristic of solvent
Relative density	At 20°C 0,71 ÷ 0,75 g/ml
Flash point	Low. 0° C
Pressure	at 20°C 5,0 ± 0,5 bar
Pressure	At 50°C 8,0 ± 0,5 bar
Solvent	Acetone
Valve	female
Compatibility	Acrylic, Nitro, Synthetic Nitro, Nitro Acrylic, synthetic fast drying.
Compatibilità to verify	Alkyd, one-component epoxy
Possibility to have other types of keys dispensers for different effects and uses	
Before using refer to the card / metering Manual cod. DOS	

ARRANGEMENTS FOR USING: this tank Spray Preloaded: add, using a special equipment for filling, the paint in the desired color, in an amount of 100 ml. Warning: the paint must not be diluted as the solvents required for dilution are already contained in the cylinder Spray Preloaded. **HOW TO USE:** After filling with filler (Cod. DOS), vigorously shake the bottle for at least 1 minute, until you hear the marbles internal move freely. You may also want to shake the can occasionally during use. First apply a thin coat to improve the coverage and adherence and thus reduce the possibility of sagging. Distance application about 20 cm. After a few moments to apply a second horizontal hand immediately followed by a third vertical hand. Allow to dry a few minutes. After use, it is recommended spraying to 2/3 seconds with the cylinder upside down, to avoid filling the dispenser. After 24 h, proceed with the normal use of the painted piece.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.