

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **V403**  
 Product name: **Tracciante Marker 360° 500 ml**  
 Chemical name and synonym: **vernice in aerosol**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Paint in aerosol**

#### 1.3. Details of the supplier of the safety data sheet

Name: **GNOCCHI ECO- SPRAY S.R.L.**  
 Full address: **Via per Pavone del Mella sn**  
 District and Country: **25020 Cigole (BS)**  
**Italia**  
 Tel. **+39 030 9959674**  
 Fax **+39 030 959265**

e-mail address of the competent person

responsible for the Safety Data Sheet: **info@gnocchiecospray.com**

#### 1.4. Emergency telephone number

For urgent inquiries refer to: **CENTRO ANTIVELENI Ospedale Niguarda tel: +39 02 66101029**

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words:

Danger

## Hazard statements:

<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H319</b>	Causes serious eye irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

## Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P211</b>	Do not spray on an open flame or other ignition source.
<b>P251</b>	Do not pierce or burn, even after use.
<b>P264</b>	Wash . . . thoroughly after handling.
<b>P280</b>	Wear eye protection / face protection.
<b>P304+P340</b>	IF INHALED: remove person to fresh air and keep comfortable for breathing.
<b>P312</b>	Call a POISON CENTER / doctor / . . . / if you feel unwell.
<b>P410+P412</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

**Contains:** ACETONE  
METHYL ACETATE

**2.3. Other hazards.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients.****3.1. Substances.**

Information not relevant.

**3.2. Mixtures.**

Contains:

<b>Identification.</b>	<b>Conc. %.</b>	<b>Classification 1272/2008 (CLP).</b>
<b>ACETONE</b>		
CAS. 67-64-1	30 - 32,5	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC. 200-662-2		
INDEX. 606-001-00-8		
<b>BUTANE</b>		
CAS. 106-97-8	19,5 - 21	Flam. Gas 1 H220, Note C U
EC. 203-448-7		
INDEX. 601-004-00-0		
<b>PROPANE</b>		
CAS. 74-98-6	19,5 - 21	Flam. Gas 1 H220, Note U
EC. 200-827-9		
INDEX. 601-003-00-5		

**METHYL ACETATE**

CAS. 79-20-9

12 - 13,5

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC. 201-185-2

INDEX. 607-021-00-X

**XYLENE (MIXTURE OF ISOMERS)**

CAS. 1330-20-7

5 - 6

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C

EC. 215-535-7

INDEX. 601-022-00-9

**ETHYLBENZENE**

CAS. 100-41-4

5 - 6

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373

EC. 202-849-4

INDEX. 601-023-00-4

**ISOBUTYL ACETATE**

CAS. 110-19-0

5 - 6

Flam. Liq. 2 H225, EUH066, Note C

EC. 203-745-1

INDEX. 607-026-00-7

**2-BUTOXYETHANOL**

CAS. 111-76-2

3 - 3,5

Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC. 203-905-0

INDEX. 603-014-00-0

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

### 6.2. Environmental precautions.

Do not disperse in the environment.

### 6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

### ACETONE

#### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1200	500	2400	1000
MAK	DEU	1200	500	2400	1000
VLA	ESP	1210	500		
VLEP	FRA	1210	500	2420	1000
WEL	GRB	1210	500	3620	1500
TLV	ITA	1210	500		
NDS	POL	600		1800	
OEL	EU	1210	500		

TLV-ACGIH	1187	500	1781	750
-----------	------	-----	------	-----

**PROPANE**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
NDS	POL	1800			
TLV-ACGIH			1000		

**BUTANE**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
VLA	ESP		800		
VLEP	FRA	1900	800		
WEL	GRB	1450	600	1810	750
NDS	POL	1900		3000	
TLV-ACGIH				2377	1000

**METHYL ACETATE**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	610	200	2440	800	
MAK	DEU	310	100	1240	400	
VLA	ESP	616	200	770	250	
VLEP	FRA	610	200	760	250	SKIN.
WEL	GRB	616	200	770	250	
NDS	POL	250		600		
TLV-ACGIH		606	200	757	250	

**ISOBUTYL ACETATE**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	DEU	480	100	960	200
VLA	ESP	724	150		
VLEP	FRA	710	150	940	200
WEL	GRB	724	150	903	187
NDS	POL	200		400	
TLV-ACGIH		713	150		

**ETHYLBENZENE**

**Threshold Limit Value.**

Type	Country	TWA/8h	STEL/15min
------	---------	--------	------------

		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN.
MAK	DEU	88	20	176	40	SKIN.
VLA	ESP	441	100	884	200	SKIN.
VLEP	FRA	88,4	20	442	100	SKIN.
WEL	GRB	441	100	552	125	SKIN.
TLV	ITA	442	100	884	200	SKIN.
NDS	POL	200		400		
OEL	EU	442	100	884	200	SKIN.
TLV-ACGIH		87	20			

**XYLENE (MIXTURE OF ISOMERS)**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN.
MAK	DEU	440	100	880	200	SKIN.
VLA	ESP	221	50	442	100	SKIN.
VLEP	FRA	221	50	442	100	SKIN.
WEL	GRB	220	50	441	100	
TLV	ITA	221	50	442	100	SKIN.
NDS	POL	100				
OEL	EU	221	50	442	100	SKIN.
TLV-ACGIH		434	100	651	150	

**2-BUTOXYETHANOL**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	49	10	196	40	SKIN.
MAK	DEU	49	10	98	20	SKIN.
VLA	ESP	98	20	245	50	SKIN.
VLEP	FRA	49	10	246	50	SKIN.
WEL	GRB	123	25	246	50	SKIN.
TLV	ITA	98	20	246	50	SKIN.
NDS	POL	98		200		
OEL	EU	98	20	246	50	SKIN.
TLV-ACGIH		97	20			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 395 mg/m3.

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

None required.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

**ENVIRONMENTAL EXPOSURE CONTROLS.**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

Appearance	aerosol
Colour	various
Odour	characteristic of solvent
Odour threshold.	n.a.
pH.	n.a.
Melting point / freezing point.	Not available.
Initial boiling point.	> Not applicable.
Boiling range.	Not available.
Flash point.	< Not applicable.
Evaporation Rate	Not available.
Flammability of solids and gases	flammable gas
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,75 - 0,80 g/ml
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	n.a.
Viscosity	Not available.
Explosive properties	not applicable
Oxidising properties	not applicable

**9.2. Other information.**

Molecular weight. 66,728



VOC (Directive 2010/75/EC) : 100,00 % - 784,00 g/litre.  
VOC (volatile carbon) : 71,24 % - 558,52 g/litre.

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL: decomposes in the presence of heat.

ACETONE: decomposes under the effect of heat.

ISOBUTYL ACETATE: decomposes under the effect of heat. Attacks various types of plastic material.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

ETHYLBENZENE: reacts violently with strong oxidising agents and attacks various types of plastics. Can form explosive mixtures with the air.

2-BUTOXYETHANOL: can react dangerously with: aluminium, oxidising agents. Forms peroxide with air.

ACETONE: risk of explosion on contact with: bromine trifluoride, difluoro dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. Can react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl chloride, chromosulphuric acid, fluorine, strong oxidising agents. Develops flammable gases with nitrosyl perchlorate.

ISOBUTYL ACETATE: risk of explosion on contact with: strong oxidising agents. Can react violently with: alkaline hydroxides, potassium tert-butoxides. Forms explosive mixtures with the air.

### 10.4. Conditions to avoid.

Avoid overheating.

2-BUTOXYETHANOL: avoid exposure to sources of heat and naked flames.

ACETONE: avoid exposure to sources of heat and naked flames.

ISOBUTYL ACETATE: avoid exposure to sources of heat and naked flames.

### 10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE: acid and oxidising substances.

ISOBUTYL ACETATE: strong oxidising agents, nitrates, strong bases and acids.

### 10.6. Hazardous decomposition products.

ETHYLBENZENE: methane, styrene, hydrogen, ethane.

2-BUTOXYETHANOL: hydrogen.

ACETONE: ketenes and other irritating compounds.

## SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

ETHYLBENZENE: like the benzene homologues, may exert an effect on the CNS with depression, narcosis, often preceded by dizziness and accompanied by headache. It is irritating to the skin, conjunctivae and respiratory apparatus.

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral).3523 mg/kg Rat

LD50 (Dermal).4350 mg/kg Rabbit

LC50 (Inhalation).26 mg/l/4h Rat

ETHYLBENZENE

LD50 (Oral).3500 mg/kg Rat

LD50 (Dermal).15354 mg/kg Rabbit

LC50 (Inhalation).17,2 mg/l/4h Rat

2-BUTOXYETHANOL

LD50 (Oral).615 mg/kg Rat

LD50 (Dermal).405 mg/kg Rabbit

LC50 (Inhalation).2,2 mg/l/4h Rat

## SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity.

Information not available.

### 12.2. Persistence and degradability.

XYLENE (MIXTURE OF ISOMERS)

Solubility in water.

mg/l 100 - 1000

Biodegradability: Information not available.

## BUTANE

Solubility in water. mg/l 0,1 - 100

Rapidly biodegradable.

## PROPANE

Solubility in water. mg/l 0,1 - 100

Rapidly biodegradable.

## ETHYLBENZENE

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

## 2-BUTOXYETHANOL

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

## ACETONE

Rapidly biodegradable.

## METHYL ACETATE

Solubility in water. 243500 mg/l

Rapidly biodegradable.

## ISOBUTYL ACETATE

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

**12.3. Bioaccumulative potential.**

## XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water. 3,12

BCF. 25,9

## BUTANE

Partition coefficient: n-octanol/water. 1,09

## PROPANE

Partition coefficient: n-octanol/water. 1,09

## ETHYLBENZENE

Partition coefficient: n-octanol/water. 3,6

## 2-BUTOXYETHANOL

Partition coefficient: n-octanol/water. 0,81

## ACETONE

Partition coefficient: n-octanol/water. -0,23  
BCF. 3

## METHYL ACETATE

Partition coefficient: n-octanol/water. 0,18

## ISOBUTYL ACETATE

Partition coefficient: n-octanol/water. 2,3  
BCF. 15,3

**12.4. Mobility in soil.**

## XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water. 2,73

## METHYL ACETATE

Partition coefficient: soil/water. 0,18

**12.5. Results of PBT and vPvB assessment.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects.**

Information not available.

**SECTION 13. Disposal considerations.****13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information.****14.1. UN number.**

ADR / RID, IMDG, 1950  
IATA:

**14.2. UN proper shipping name.**

ADR / RID: AEROSOLS,  
FLAMMABLE  
IMDG: AEROSOLS  
IATA: AEROSOLS,  
FLAMMABLE

**14.3. Transport hazard class(es).**

ADR / RID: Class: 2 Label: 2.1  
IMDG: Class: 2 Label: 2.1  
IATA: Class: 2 Label: 2.1

**14.4. Packing group.**

ADR / RID, IMDG, -  
IATA:

**14.5. Environmental hazards.**

ADR / RID: NO  
IMDG: NO  
IATA: NO

**14.6. Special precautions for user.**

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
		Maximum quantity: 150 Kg	Packaging instructions: 203
IATA:	Cargo:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Pass.:	A145, A167, A802	
	Special Instructions:		

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.**

Information not relevant.

## SECTION 15. Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 8

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.  
Point. 40

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3

<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament

- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**Changes to previous review:**

The following sections were modified:

02 / 09 / 15.