



## Tracing paint 90° (V401)

Do you need to trace walls, asphalts, cements, woods, floors? This spray included in the Ambro-Sol "Paint" line is for you! It resists to bad weather and it's available in different colors.

**TRACING PAINT** - Spray paint for special marking on brickwork, flooring, asphalt, cement and wood. This product has a high weathering and wear resistance. Available in standard colors.



### Technical specifications:

Quantity	400 ml
Confection	12 Pz.
Aspect	Cylinder containing under pressure fluid
Colour	Various
Odour	Typical of solvent
Relative density	At 20°C 0,71 ÷ 0,75 g/ml
Flash point	Low. 0° C
Writings on the cylinder bottom	Barcode, date of production, name of product
Pressure	at 20°C 5,5 ± 1, bar
Pressure	at 50°C 8,0 ± 0,5 bar
Viscosity ford cup	From 10" to 13"
Dry residual in the cylinder	From 30% to 35%
Brilliance	from 10 to 15 Gloss (glossmeter angol 60°)
Operating temperature	-10°C / +100°C (Peaks 150° C)
Drying times:	Out dust 10 minutes
	Dry to touch 15 minutes
	Dry in depth 22 hours
Possibility to have other types of keys dispensers for different effects and uses	
Token dye reference	
Re-coating at all times.	
Fields of application: wood surfaces, metal surfaces such as iron, aluminum, steel, glass and plastics.	
Product subjected to Directive C.O.V. Subcategory: Finishing Special Value Limit VOC: 840 g / liter max actual content: 640 g / liter	

**HOW TO USE:** clean carefully the piece to be treated, open the cap, shake the bottle vigorously for at least 1 minute, until you hear the internal marbles move freely. High viscosity product, so you may also want to occasionally shake the bottle well during use. After use, it is recommended spraying to 2.3 seconds with the cylinder upside-down, to prevent blocking of the dispenser. To remove the product use nitro and / or acetone.

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

#### Hazards identification:

H222	<b>Extremely flammable aerosol.</b>
H229	<b>Pressurized container: may burst if heated.</b>
H319	<b>Causes serious eye irritation.</b>
H336	<b>May cause drowsiness or dizziness</b>
EUH066	<b>Repeated exposure may cause skin dryness or cracking.</b>

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.