



Silicon sealant remover 200 ml (P325)

This spray is ideal for both professional and domestic uses and do-it-yourself users as well. It removes rapidly silicone, without ruin surfaces, it leaves them in their natural brilliance.

SILICON SEALANT REMOVER – Mix of solvents designed to remove excess silicone or silicone scraps. The product acts quickly in the presence of fresh silicone and slower in the presence of hardened silicone. When large amounts of silicone need to be removed remove as much as possible before applying the solvent. It does not corrode or tarnish any surface.

Technical Specifications:

| | |
|--------------------|---|
| Barcode | EAN: 8034108893754 |
| Quantity | 200 ml |
| Confection | 12 Pz. |
| Aspect | Cylinder containing under pressure fluid |
| Color | Light white |
| Odour | Characteristic of solvent |
| Relative density | a 20°C 0,68 ÷ 0,72 g/ml |
| Flash point | Low. 0° C |
| Pressure at 20°C | 4/6 bar |
| Water solubility | Not soluble |
| Solvent solubility | Total |
| Viscosity at 100°C | 3,8 cSt (dry residual) |
| Melting point | 52-62°C (dry residual) |
| Penetration test | <= 30 dmm (25°C) (dry residual) |
| Observations | Product with gel technology, it does not drip |



HOW TO USE : *Fresh silicone*: Shake well before use and spray the surface from a distance of about 15 cm, leave to act for some minutes and then use a cloth or a spatula. *Silicone hardened*: Scrape the biggest parts with a razor blade or a spatula. Shake well before use and spray the surface from a distance of about 15 cm and let the product to act for a few minutes. Remove with a rag or a spatula. Repeat if necessary.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.
After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

| | |
|------|---|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurized container: may burst if heated. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.