W503 - Water based antispatter for welding 400 ml

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 1/10

# Safety data sheet

#### SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: W503

Product name
Chemical name and synonym

Antispruzzi per saldature base acqua distaccante per saldatura base H2O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Anti-spatter

1.3. Details of the supplier of the safety data sheet

Name GNOCCHI ECO- SPRAY S.R.L. Full address Via per Pavone del Mella sn

District and Country 25020 Cigole (BS)

Italia

Tel. +39 030 9959674 Fax +39 030 959265

e-mail address of the competent person

responsible for the Safety Data Sheet info@gnocchiecospray.com

1.4. Emergency telephone number

For urgent inquiries refer to CENTRO ANTIVELENI Ospedale Niguarda tel: +39 02 66101029

#### **SECTION 2. Hazards identification.**

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words: Danger

W503 - Water based antispatter for welding 400 ml

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 2/10

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

Precautionary statements:

Hazard statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

#### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### **SECTION 3. Composition/information on ingredients.**

#### 3.1. Substances.

Information not relevant.

#### 3.2. Mixtures.

Contains:

DME

Identification. Conc. %. Classification 1272/2008

(CLP).

CAS. 115-10-6 50 - 54 Flam. Gas 1 H220, Press.

Gas H280

EC. 204-065-8

INDEX. 603-019-00-8

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures.**

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 3/10

### W503 - Water based antispatter for welding 400 ml

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

#### **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

#### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### SECTION 6. Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

#### 6.2. Environmental precautions.

Do not disperse in the environment.

#### 6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 4/10

### W503 – Water based antispatter for welding 400 ml

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

#### **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

#### 7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

#### 7.3. Specific end use(s).

Information not available.

#### **SECTION 8. Exposure controls/personal protection.**

#### 8.1. Control parameters.

Information not available.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

#### HAND PROTECTION

None required.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 5/10

### W503 - Water based antispatter for welding 400 ml

environmental standards.

#### **SECTION 9. Physical and chemical properties.**

#### 9.1. Information on basic physical and chemical properties.

Appearance aerosol Colour white Odour odourless Odour threshold. Not available. Not available. Melting point / freezing point. Not available. Initial boiling point. < Not applicable. Not available. Boiling range. Flash point. < Not applicable. **Evaporation Rate** Not available. Flammability of solids and gases flammable gas Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available Vapour pressure. Not available. Vapour density Not available. Relative density. 0,812 Kg/l Solubility soluble in water Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available. Viscosity Not available. Explosive properties not applicable Oxidising properties not applicable

#### 9.2. Other information.

Solid content. 10,00 %

VOC (Directive 2010/75/EC) : 50,00 % - 406,00 g/litre. VOC (volatile carbon) : 26,05 % - 211,50 g/litre.

#### **SECTION 10. Stability and reactivity.**

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

POLYETHYLENGLYCOL: decomposes slowly at high temperatures in the presence of air.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 6/10

## W503 – Water based antispatter for welding 400 ml

10.4. Conditions to avoid.

Avoid overheating.

#### 10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

POLYETHYLENGLYCOL: avoid contact with oxidising agents and concentrated inorganic acids.

#### 10.6. Hazardous decomposition products.

Information not available.

#### **SECTION 11. Toxicological information.**

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.

#### 11.1. Information on toxicological effects.

Information not available.

#### **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity.

Information not available.

#### 12.2. Persistence and degradability.

POLYETHYLENGLYCOL

Solubility in water. > 10000 mg/l

#### 12.3. Bioaccumulative potential.

POLYETHYLENGLYCOL

Partition coefficient: n- -2,2972

octanol/water.

BCF. 3,2

#### 12.4. Mobility in soil.

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 7/10

### W503 - Water based antispatter for welding 400 ml

**POLYETHYLENGLYCOL** 

Partition coefficient:

1

soil/water.

#### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.

### **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

#### **SECTION 14. Transport information.**

#### 14.1. UN number.

ADR / RID, IMDG, 1950

IATA:

#### 14.2. UN proper shipping name.

ADR / RID: AEROSOLS,

FLAMMABLE

IMDG: AEROSOLS
IATA: AEROSOLS,

AEROSOLS, FLAMMABLE

#### 14.3. Transport hazard class(es).

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



#### 14.4. Packing group.

W503 - Water based antispatter for welding 400 ml

Revision nr. 7 Dated 23/02/2016

Printed on 25/02/2016

Page n. 8/10

ADR / RID, IMDG,

14.5. Environmental hazards.

IATA:

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: --Limited Tunnel Quantities: 1

restriction code: (D)

Special Provision: -

IMDG: EMS: F-D, S-U Limited

Quantities: 1

Maximum

IATA: Cargo:

Pass.:

Packaging quantity: 150 instructions: 203

Kg Maximum quantity: 75

Packaging instructions: 203

Kg A145, A167, Special Instructions:

A802

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

#### **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

40 Point.

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

W503 - Water based antispatter for welding 400 ml

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 9/10

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

#### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

#### **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1 Flammable gas, category 1

Aerosol 1 Aerosol, category 1 Aerosol 3 Aerosol, category 3 Press. Gas Pressurised gas

H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may burst if heated.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

Revision nr. 7

Dated 23/02/2016

Printed on 25/02/2016

Page n. 10/10

### W503 - Water based antispatter for welding 400 ml

- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

09 / 11 / 15.