

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: A473
Product name: Lava Motori
Chemical name and synonym: Sgrassante

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: cleaner

1.3. Details of the supplier of the safety data sheet

Name: GNOCCHI ECO- SPRAY S.R.L.
Full address: Via per Pavone del Mella sn
District and Country: 25020 Cigole (BS)
Italia
Tel. +39 030 9959674
Fax +39 030 959265

e-mail address of the competent person

responsible for the Safety Data Sheet: info@gnocchiecospray.com

1.4. Emergency telephone number

For urgent inquiries refer to: CENTRO ANTIVELENI Ospedale Niguarda tel: +39 02 66101029

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P264	Wash . . . thoroughly after handling.
P280	Wear eye protection / face protection.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER / doctor / . . . / if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

Contains:	N-BUTYL ACETATE ACETONE PROPAN-2-OL
------------------	---

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
N-BUTYL ACETATE		
CAS. 123-86-4	35 - 37,5	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC. 204-658-1		
INDEX. 607-025-00-1		
BUTANE		
CAS. 106-97-8	15 - 16,5	Flam. Gas 1 H220, Note C U
EC. 203-448-7		
INDEX. 601-004-00-0		
PROPANE		
CAS. 74-98-6	15 - 16,5	Flam. Gas 1 H220, Note U
EC. 200-827-9		
INDEX. 601-003-00-5		

ACETONE

CAS. 67-64-1

15 - 16,5

Flam. Liq. 2 H225, Eye Irrit. 2
H319, STOT SE 3 H336,
EUH066

EC. 200-662-2

INDEX. 606-001-00-8

CARBON DIOXIDE

CAS. 124-38-9

9 - 10,5

Substance with a community
workplace exposure limit.

EC. 204-696-9

INDEX. -

PROPAN-2-OL

CAS. 67-63-0

10 - 11,5

Flam. Liq. 2 H225, Eye Irrit. 2
H319, STOT SE 3 H336

EC. 200-661-7

INDEX. 603-117-00-0

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.**4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.**5.1. Extinguishing media.****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters.**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.**6.1. Personal precautions, protective equipment and emergency procedures.**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions.

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.**7.1. Precautions for safe handling.**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.**8.1. Control parameters.**

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

N-BUTYL ACETATE**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	DEU	480	100	960	200
VLA	ESP	724	150	965	200
VLEP	FRA	710	150	940	200
WEL	GRB	724	150	966	200
NDS	POL	200		950	
TLV-ACGIH		713	150	950	200

ACETONE**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1200	500	2400	1000
MAK	DEU	1200	500	2400	1000
VLA	ESP	1210	500		
VLEP	FRA	1210	500	2420	1000
WEL	GRB	1210	500	3620	1500
TLV	ITA	1210	500		
NDS	POL	600		1800	
OEL	EU	1210	500		

A473 – Engine motor cleaner

TLV-ACGIH	1187	500	1781	750
-----------	------	-----	------	-----

PROPANE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
NDS	POL	1800			
TLV-ACGIH			1000		

BUTANE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
VLA	ESP		800		
VLEP	FRA	1900	800		
WEL	GRB	1450	600	1810	750
NDS	POL	1900		3000	
TLV-ACGIH				2377	1000

PROPAN-2-OL

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	500	200	1000	400
MAK	DEU	500	200	1000	400
VLA	ESP	500	200	1000	400
VLEP	FRA			980	400
WEL	GRB	999	400	1250	500
NDS	POL	900		1200	
TLV-ACGIH		492	200	983	400

CARBON DIOXIDE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	9100	5000	18200	10000
MAK	DEU	9100	5000	18200	10000
VLA	ESP	9150	5000		
WEL	GRB	9150	5000	27400	15000
TLV	ITA	9000	5000		
NDS	POL	9000		27000	
OEL	EU	9000	5000		
TLV-ACGIH		9000	5000	54000	30000

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 731 mg/m³.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	aerosol
Colour	colourless
Odour	characteristic of solvent
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not applicable.
Boiling range.	Not available.
Flash point.	Not applicable.
Evaporation Rate	Not available.
Flammability of solids and gases	flammable gas
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	Not available.

Solubility	insoluble
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information.

Molecular weight.	75,112
VOC (Directive 2010/75/EC) :	100,00 %
VOC (volatile carbon) :	64,34 %

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

ACETONE: decomposes under the effect of heat.

N-BUTYL ACETATE: decomposes readily with water, especially when warm.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

ACETONE: risk of explosion on contact with: bromine trifluoride, difluoro dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. Can react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl chloride, chromosulphuric acid, fluorine, strong oxidising agents. Develops flammable gases with nitrosyl perchlorate.

N-BUTYL ACETATE: risk of explosion on contact with: strong oxidising agents. Can react dangerously with alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating.

ACETONE: avoid exposure to sources of heat and naked flames.

N-BUTYL ACETATE: avoid exposure to moisture, sources of heat and naked flames.

10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE: acid and oxidising substances.

N-BUTYL ACETATE: water, nitrates, strong oxidising agents, acids and alkalis and potassium tert-butoxide.

10.6. Hazardous decomposition products.

ACETONE: ketenes and other irritating compounds.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

N-BUTYL ACETATE: in humans the substance's vapours cause irritation to the eyes and nose. In the event of repeated exposure, there is skin irritation, dermatosis (with dryness and flaking of the skin) and keratitis.

PROPAN-2-OL

LD50 (Oral). 4710 mg/kg Rat

LD50 (Dermal). 12800 mg/kg Rat

LC50 (Inhalation). 72,6 mg/l/4h Rat

N-BUTYL ACETATE

LD50 (Oral). > 6400 mg/kg Rat

LD50 (Dermal). > 5000 mg/kg Rabbit

LC50 (Inhalation). 21,1 mg/l/4h Rat

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

BUTANE

Solubility in water. mg/l 0,1 - 100

Rapidly biodegradable.

PROPANE

Solubility in water. mg/l 0,1 - 100

Rapidly biodegradable.

PROPAN-2-OL

Rapidly biodegradable.

ACETONE

Rapidly biodegradable.

N-BUTYL ACETATE

Solubility in water. mg/l 1000 - 10000

12.3. Bioaccumulative potential.

BUTANE

Partition coefficient: n-octanol/water. 1,09

PROPANE

Partition coefficient: n-octanol/water. 1,09

PROPAN-2-OL

Partition coefficient: n-octanol/water. 0,05

ACETONE

Partition coefficient: n-octanol/water. -0,23

BCF. 3

N-BUTYL ACETATE

Partition coefficient: n-octanol/water. 2,3

BCF. 15,3

12.4. Mobility in soil.

N-BUTYL ACETATE

Partition coefficient: soil/water. < 3

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name.

ADR / RID: AEROSOLS,
FLAMMABLE
IMDG: AEROSOLS
IATA: AEROSOLS,
FLAMMABLE

14.3. Transport hazard class(es).

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



14.4. Packing group.

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards.

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: -- Limited Tunnel

		Quantities: 1 L	restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**Seveso category. 8Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.Product.
Point. 40Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.