

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: I256/GRAFF
 Product name: Graffiti remover 400 ml
 Chemical name and synonym: Remover

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Spray to remove graffiti from a variety of surfaces.

Identified Uses	Industrial	Professional	Consumer
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name: AMBRO-SOL S.R.L.
 Full address: Via per Pavone del Mella n.21
 District and Country: 25020 Cigole (BS)
 Italia
 Tel. +39 030 9959674
 Fax +39 030 959265

e-mail address of the competent person

responsible for the Safety Data Sheet: quality@ambro-sol.com

1.4. Emergency telephone number

For urgent inquiries refer to

Centro Antiveleni di Pavia: 0382 24444 (IRCCS Fondazione Maugeri - Pavia)
 Centro Antiveleni di Bergamo: 800 883300 (Ospedali Riuniti - Bergamo)
 Centro Antiveleni di Firenze: 055 7947819 (Ospedale Careggi - Firenze)
 Centro Antiveleni di Roma: 06 3054343 (Policlinico Gemelli - Roma)
 Centro Antiveleni di Napoli: 081 7472870 (Ospedale Cardarelli - Napoli)
 Centro de Información Toxicológica en España: 91 5620420 (Inst. Nacional de Toxicología y Ciencias Forenses)
 Centre Antipoison en France: 01 40054848 (Centre Antipoison et de Toxicovigilance de Paris)
 Pomorskie Centrum Toksykologii ul. Kartuska 4/6, 80-104 Gdańsk tel./fax: (58) 682 04 04
 American Association of Poison Control Centers: +1 (800) 222-1222
 Giftkontrollzentrum Berlin, Brandenburg 030 – 19 240

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Acute toxicity, category 4	H302	Harmful if swallowed.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 2	H371	May cause damage to organs.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H371	May cause damage to organs.

Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

Contains: METHYLAL

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.1. Substances**

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
Dimethyl ether		
CAS 115-10-6	39 ≤ x < 43	Flam. Gas 1 H220, Press. Gas H280
EC 204-065-8		

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
POL	Polska	ROZPORZADZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2017

Dimethyl ether

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
OEL	EU	1920	1000		

Predicted no-effect concentration - PNEC

Normal value in fresh water	155	µg/l
Normal value in marine water	16	µg/l
Normal value for fresh water sediment	681	µg/kg/d
Normal value for marine water sediment	69	µg/kg/d
Normal value of STP microorganisms	160	mg/l
Normal value for the terrestrial compartment	45	µg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		NPI				
Inhalation		VND		471 mg/m3		VND		1894 mg/m3
Skin		NPI		NPI		NPI		NPI

1,3 DIOXALANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	310	100	620	200
MAK	DEU	310	100	620	200
VLA	ESP	61	20		
NDS	POL	10		50	
TLV-ACGIH		61		20	

Predicted no-effect concentration - PNEC

Normal value in fresh water	19,7	mg/l
Normal value in marine water	1,97	mg/l
Normal value for fresh water sediment	77,7	mg/kg/d
Normal value for marine water sediment	7,77	mg/kg/d

I256/GRAFF - Graffiti remover 400 ml

Normal value for water, intermittent release	950	µg/l
Normal value of STP microorganisms	1	mg/l
Normal value for the terrestrial compartment	2,62	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,8 mg/kg p.c.				
Inhalation	NPI	NPI	NPI	5,7 mg/mc	NPI	NPI	NPI	18,09 mg/m3
Skin	NPI	NPI	NPI	75 mg/kg p.c.	NPI	NPI	NPI	4,1 mg/kg bw/d

METHYLAL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	960	300	1920	600
VLA	ESP	3165	1000		
VLEP	FRA	3100	1000		
WEL	GBR	3160	1000	3950	1250
NDS	POL	1000		3500	
TLV-ACGIH		3112	1000		

Predicted no-effect concentration - PNEC		
Normal value in fresh water	14,57	mg/l
Normal value in marine water	1,45	mg/l
Normal value for fresh water sediment	13,135	mg/kg/d
Normal value for marine water sediment	1,31	mg/kg/d
Normal value of STP microorganisms	10	g/l
Normal value for the terrestrial compartment	4,65	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		18,1 mg/kg bw/d				
Inhalation	NPI	NPI	NPI	31,5 mg/m3	NPI	NPI	NPI	126,6 mg/m3
Skin	NPI	NPI	NPI	18,1 mg/kg bw/d	NPI	NPI	NPI	17,9 mg/kg bw/d

Hydrocarbons, C9, aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
OEL	EU	100	20		
TLV-ACGIH			25		

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral								11 mg/kg bw/d
Inhalation				32 mg/m3				150 mg/m3

Skin	11 mg/kg bw/d	25 mg/kg bw/d
------	------------------	------------------

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
 VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	aerosol
Colour	transparent
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	flammable gas
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available

Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	20°C 0,84 ÷ 0,90 g/ml
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information

VOC (Directive 2010/75/EC) :	88,86 % - 773,04 g/litre
VOC (volatile carbon) :	44,41 % - 386,39 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

1242,39 mg/kg

LD50 (Dermal) of the mixture:

Not classified (no significant component)

METHYLAL

LD50 (Oral) 6423 mg/kg Rat - Wistar

LD50 (Dermal) > 5000 mg/kg Rabbit - New Zeland white

LC50 (Inhalation) 57 mg/l Mouse - Swiss

1,3 DIOXALANE

LD50 (Oral) > 2000 mg/kg Rat

LD50 (Dermal) 15000 mg/kg rabbit

LC50 (Inhalation) 68,4 mg/l rat 1 h

Dimethyl ether

LC50 (Inhalation) 164000 ppm rat

Hydrocarbons, C9, aromatics

LD50 (Oral) 3492 mg/kg rat

LD50 (Dermal) 3160 mg/kg rabbit

LC50 (Inhalation) 6193 mg/l/4h rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause damage to organs

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

METHYLAL

LC50 - for Fish	> 1000 mg/l/96h Danio rerio
EC50 - for Crustacea	> 1000 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	9,12 g/l/72h
Chronic NOEC for Fish	450,281 mg/l 30 days
Chronic NOEC for Crustacea	150,5 mg/l 30 days
Chronic NOEC for Algae / Aquatic Plants	145,77 mg/l 30 days

1,3 DIOXALANE

LC50 - for Fish	> 95,4 mg/l/96h <i>Lepomis macrochirus</i>
EC50 - for Crustacea	> 772 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	> 877 mg/l/72h <i>Pseudokirchnerella subcapitata</i>
Chronic NOEC for Fish	546,3 mg/l 30 days
Chronic NOEC for Crustacea	197,4 mg/l EC10 / LC10 or NOEC for freshwater invertebrates
Chronic NOEC for Algae / Aquatic Plants	877 mg/l EC10 / LC10 or NOEC for freshwater algae

Dimethyl ether

LC50 - for Fish	> 4000 mg/l/96h <i>Poecilia reticulata</i>
EC50 - for Crustacea	> 4000 mg/l/48h <i>Daphnia magna</i>
Chronic NOEC for Fish	4,1 g/l 4 days
Chronic NOEC for Crustacea	4,4 g/l 48 h

Hydrocarbons, C9, aromatics

LC50 - for Fish	> 92 mg/l/96h
EC50 - for Crustacea	> 32 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 29 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	70 µg/l

12.2. Persistence and degradability

METHYLAL

Solubility in water	> 10000 mg/l
NOT rapidly degradable	

Under test conditions no biodegradation observed (100%).

1,3 DIOXALANE

Degradability: information not available

under test conditions no biodegradation observed.

Dimethyl ether

NOT rapidly degradable

Under test conditions no biodegradation observed (100%)

Hydrocarbons, C9, aromatics

Rapidly degradable

12.3. Bioaccumulative potential

METHYLAL

Partition coefficient: n-octanol/water	0,18
BCF	0,6

1,3 DIOXALANE

Partition coefficient: n-octanol/water	-0,31
--	-------

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Dimethyl ether

Given the high rate of disappearance of the solution, it is unlikely that the product constitutes a significant hazard to aquatic life. Potential ozone-depleting effect: 0. Global warming potential (GWP): 1.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Product residues are considered hazardous special waste. Do not dispose of in wastewater.

Empty cylinders, although completely emptied, should not be dispersed in the environment.

The overheated aerosol container at a temperature above 50 °C may burst even if it contains a small gas residue.

Waste transport may be subject to ADR.

Refer to applicable regulations.

European Waste Catalog (contaminated containers):

Aerosol as a household waste is excluded from the application of the above standard.

The exhausted commercial / industrial aerosol can be classified as: 15.01.10 *: packaging containing residues of dangerous or contaminated substances.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards

ADR / RID: NO
 IMDG: NO
 IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 200 Kg	Packaging instructions: 677
	Pass.:	Maximum quantity: 100 Kg	Packaging instructions: 670
	Special Instructions:	-	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas	Pressurised gas
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number

- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.